








Guanti di protezione

Guanti di protezione corrispondenti a quanto prescritto dalla direttiva 92/58/CEE - UNI 7543 - ISO 3864, cui fa riferimento il D.Lgs.493/96, trafuso nel nuovo D.Lgs. 81/08.

La certificazione identifica la normativa di sicurezza alla quale il guanto risponde ed e' esplicitata da una serie di valori che ne riassumono le performances. Ad un numero alto corrisponde un alto livello di prestazione.

Pittogrammi stampati su guanti conformi alla direttiva su i D.P.I. (Dispositivi di Protezione Individuale):

CE	Indica che il guanto risponde a delle esigenze di rischi minori ed intermedi, e che può circolare liberamente nel mercato europeo.
CE 0000	I guanti per rischi irreversibili o mortali, dopo il logo CE dovranno riportare un numero che identifichi l'ente che ha effettuato il controllo di qualità.
Categoria I	D.P.I. di disegno semplice per salvaguardare le persone da rischi fisici di lieve entità.
Categoria II	D.P.I. di disegno intermedio che salvaguarda l'operatore dai rischi medi.
Categoria III	D.P.I. di disegno completo, destinato a salvaguardare da rischi di morte, lesioni gravi e permanenti.
EN 420	Questa norma specifica i requisiti generali di ergonomia, realizzazione dei guanti, alta visibilità, innocuità, pulizia, confort ed efficienza, marcatura ed istruzioni. Si applica a tutti i guanti di protezione e ai guanti permanentemente contenuti, in contenitori chiusi. Non si applica ai guanti per elettricista e ai guanti chirurgici.
EN 388  ABCD	Guanti di protezione contro i rischi meccanici A) Resistenza all'abrasione da 0 a 4. B) Resistenza taglio da lama da 0 a 5. C) Resistenza alla lacerazione da 0 a 4. D) Resistenza alla perforazione da 0 a 4.
EN 374 	Guanti di protezione contro i rischi chimici
EN 374 	Guanti di protezione contro i rischi da microorganismi
EN 374 	Guanti di bassa protezione contro i rischi chimici
EN 407  ABCDEF	Guanti di protezione contro i rischi da calore e/o fiamma A) Resistenza all'infiammabilità da 1 a 4. B) Resistenza al calore da contatto da 1 a 4. C) Resistenza al calore convettivo da 1 a 4. D) Resistenza al calore radiante da 1 a 4. E) Resistenza a piccole proiezioni di metallo fuso da 1 a 4. F) Resistenza ad importanti proiezioni di metallo fuso da 1 a 4.
EN 511  ABC	Guanti di protezione contro i rischi da freddo A) Resistenza al fresco convettivo da 1 a 4. B) Resistenza al calore da contatto da 1 a 4. C) Impermeabilità all'acqua da 0 a 1.
	Guanto per uso alimentare.

Mechanix Utility multipurpose gloves



- Multi-purpose technical gloves for a range of applications. Made with top-quality technical material, they are comfy, sensitive, breathable and stand out for exceptional durability, good fit and great comfort.
- Recommended for all work areas, from mechanics to body work, metal structural work, workshops for vehicle electricians, tyre fitters, construction and the installation of metal structures, etc.
- Made with palm in robust, dirt proof, synthetic leather. Back in breathable stretch fabric to keep hands cool and dry, even in very warm climates. Elastic wrist fastening with Velcro to keep the glove close fitting and allowing hand movement in the utmost comfort.
- Machine washable. Compliant with EN 388 standards with 3131 protection grade.



Code	Desc.	Taglia
4460000408	8717S	7-S
4460000410	8717M	8-M
4460000420	8717L	9-L
4460000430	8717XL	10-XL
4460000435	8717XXL	11-XXL

Leather gloves flower



- Leather Gloves flower calf.
- White, does not stain the skin.
- Tighten internal elastic wrist.
- Ideal for various jobs in the workshop and to maneuver pieces dry.
- A CE cat. II.

Code	Desc.	Taglia
4460000348	8715/8	M
4460000350	8715/9	L
4460000355	8715/10	XL
4460000360	8715/11	XXL

Guanti in pelle fiore



- Guanti in pelle fiore di vitello.
- Colore bianco, non macchia la pelle.
- Stringipolso elastico interno.
- Ideali per lavori vari in officina e per manovrare pezzi asciutti.
- A norme CE cat. II.

Code	Desc.	L mm	Taglia
4460000289	8602-8	240	8
4460000290	8602-9	240	9
4460000300	8602-10	240	10
4460000305	8602-11	240	11

Grain leather gloves padded



- Gloves grain leather calf.
- White, does not stain the skin.
- Tighten internal elastic wrist.
- Ideal for various jobs in the workshop and to maneuver any piece dry.
- Interior padding sweatshirt.
- Recommended in cold places.
- In accordance with CE cat. II.

Code	Desc.	Length mm	Taglia
4460000270	8601-9	240	9
4460000280	8601-10	240	10
4460000283	8601-11	240	11

Grain leather and cotton gloves



- Grain leather and cotton gloves.
- White, does not stain the skin.
- Back and cuff in cotton.
- Suitable for handling crates, cartons, storage operations, loading and unloading.
- Ideal for all general maintenance.
- Glove with palm, thumb and saves nails, leather.
- In accordance with CE cat. The only minimal risks.

Code	Desc.	Length mm	Taglia
4460000250	8600-9	240	9
4460000260	8600-10	240	10

Grain leather and cotton gloves with Velcro



- Work gloves pig grain leather cotton back.
- Suitable for handling crates, cartons, storage operations, loading and unloading and for all maintenance in general.
- Velcro closure can be easily adapted to any size of wrist, which guarantees a secure closure with some added comfort.
- Excellent sensitivity '.
- Glove size 8 comes in red, yellow for the other two measures.
- A CE cat. I.

Code	Desc.	Taglia
4460018940	19675/M	8-M
4460018950	19675/L	9-L
4460018970	19675/XL	10-XL
4460018980	19675/XXL	11-XXL

Gloves in crust and canvas



- Gloves in cowhide split.
- Back in denim and canvas hose.
- Elastic on the back.
- For their convenience 'they are suitable for general work and highly appreciated by dispatchers and storekeepers.
- A CE cat. I.

Code	Desc.	L mm	Taglia
4720008100	192	270	10

Gloves crusted veal



- Gloves all entirely crusted veal.
- Palm and reinforced thumb.
- Hose of 15 cm.
- Ideal for carpentry work.
- A CE cat. I.

Code	Desc.	L mm	Taglia
4460000310	8603	260	10

Gloves in crust for welders



- Split leather gloves for welders.
- Felt-lined cotton fabric.
- With saves seams.
- A CE cat. I.
- Product suitable for welding, foundry, handling of metallurgical products.

Code	Desc.	L mm	Taglia
4460007400	4017	320	10

Guanti anticalore in poliestere rivestiti in nitrile 250°C



- Guanti anticalore in tessuto jersey di cotone e poliestere con interno in feltro di poliestere, spalmatura esterna in nitrile antiscivolo. Ideali per lavorazioni con oggetti caldi fino a +250°C.
- Comodissimi e molto protettivi, adatti per lunghi tempi di lavorazione. Indicati per le industrie dello stampaggio della plastica e del vetro, forni industriali, industria metallurgica, fonderie, acciaierie, manipolazione di stampi e di lastre metalliche, lavorazioni a contatto con materiali taglienti e abrasivi.
- Offrono, oltre all'isolamento dal calore da contatto, anche una buona presa e buone caratteristiche antistrappo ed anti abrasione. La lunghezza della manichetta permette di proteggere efficacemente anche gli avambracci.

Code	Description	L mm	Taglia
4460000480	Guanti WT	350	10

Guanti anticalore in Kevlar® e cotone 350°C



- Guanti anticalore in filo continuo di Kevlar® esterno e cotone interno, che offrono un'eccezionale resistenza al taglio, alla lacerazione, all'infiammabilità e al calore da contatto.
- Comodissimi e molto protettivi, adatti per lunghi tempi di lavorazione. Indicati per le industrie dello stampaggio della plastica e del vetro, forni industriali, industria metallurgica, fonderie, acciaierie, manipolazione di stampi e di lastre metalliche, lavorazioni a contatto con materiali taglienti e abrasivi anche in presenza di oli e grassi. Idonei per la protezione dalla fiamma viva.
- L'assenza di cuciture nei punti di sforzo li rende estremamente confortevoli ed evita ogni irritazione, oltre ad evitare rotture premature dei guanti. La

Code	Description	L mm	Taglia
4460000490	Guanti KW	340	10

Nitrile gloves heavy ventilated back



- Ventilated back.
- Excellent resistance to abrasion and cutting.
- Good hygiene guaranteed by the processing performed on the cotton lining.
- Version with cotton back and cuff canvas.
- The nitrile coating is not altered in the presence of oils and fats.
- Ideal for machining in the mechanical / Built.
- A CE - Cat. II.

Code	Desc.	L mm	Taglia
4460006810	4001	250	9

Guanti in nitrile pesante interamente spalmati



- Interamente spalmati
- Ottima resistenza all'abrasione, idrocarburi e derivati, oli e grassi
- Con trattamento antibatterico Sanized R(Registrato)
- Manichetta di sicurezza in tela di cotone
- A norme CE cat II

Code	Desc.	L mm	Taglia
4460006815	4002/9	260	9

Nitrile fully coated heavy



- Entirely coated.
- Excellent resistance to abrasion and cutting.
- Good hygiene guaranteed by the processing performed on the cotton lining.
- Canvas cuff.
- The nitrile coating is not altered in the presence of oils and fats.
- Ideal for machining in the mechanical / Built and for use in the food industry.
- A CE cat. II.

Code	Desc.	L mm	Taglia
4460006820	4002	260	10

Nitrile gloves



- Nitrile gloves with cotton interlock lining.
- Lightness and maneuverability.
- Free of silicones.
- Ideal for work in the workshop, in light carpentry, the packaging sector, in the public services, the shippers.
- A CE cat. II.

Code	Desc.	L mm	Taglia
4460007430	4020	235	9

Nitrile gloves light



- Excellent abrasion resistance as well as greases and oils.
- Model with ventilated back to the breathing of the hand.
- Elasticized wrist.
- Free of silicones, ensure absolute cleanliness in metalworking.
- Ideal for work in the workshop, building, cleaning companies, plumbing and carpentry.
- A CE - CAT. II.

Code	Desc.	L mm	Taglia
4460006830	4003-S	270	8
4460006840	4004-M	270	9
4460006850	4005-L	270	10

Gloves coated with nitrile palm gray



- Gloves polyester back with the palm and fingertips coated with nitrile.
- Particularly suitable in the field of plumbing, mechanics, carpentry, maintenance, electronics, components and construction.
- The light coat nitrile glove on the hand gives the user a high dexterity.
- Highly breathable glove on the back and high resistance break.
- In accordance with CE cat. II

Code	Desc.	Taglia
4460030810	32250 - S	7/S
4460030820	32250 - M	8/M
4460030830	32250 - L	9/L
4460030840	32250 - XL	10/XL

Nitrile gloves coated with black palm



- Gloves back in nylon with palm and fingertips lightly coated with nitrile.
- Ideal for the plumbing industry, mechanics, carpentry, maintenance and construction.
- Highly breathable glove on the back and considerable resistance on the palm.
- The coated nitrile black favors the grip and abrasion resistance.
- A CE cat. II.

Code	Description	Taglia	Length mm
4460019370	19720-M-smear NITRILE GLOVE BLACK	8	240
4460019380	19720-XLQUANTO smear NITRILE BLACK	9	240
4460019390	19720-XL-smear NITRILE GLOVE BLACK	10	240

Polyurethane coated gloves gray



- Gloves with palm coated in polyurethane and knit back.
- Particularly suitable in the fields of assembly, mechanical maintenance, mechanical precision.
- Aerated back to improve breathability of the hand, elastic wristband finished in different colors depending on the size.
- Product specially created for maximum strength and remarkable sensitivity 'than reusable gloves.
- A CE cat. II.

Code	Description	Taglia	Leng. mm
4460019340	19710-M-smearred GLOVE POLYURETHANE GREY	8	240
4460019350	19710-L-smearred GLOVE POLYURETHANE GREY	9	240
4460019360	19710-XL-smearred GLOVE POLYURETHANE GREY	10	240

Gloves coated in polyurethane



- Knitted glove built with continuous filament nylon.
- Ventilated back to minimize perspiration.
- Wrist and back stretch.
- Palm coated in polyurethane.
- Use sectors: assembly workshops mechanics, precision mechanics, maintenance assembly.
- The special elasticity of the glove allows a sensitivity superior to all reusable gloves.

Code	Desc.	Taglia	Leng. mm
4460010010	4339-M	8/M	240
4460010020	4339-L	9/L	240
4460010030	4339-XL	10/XL	240

Guanti antitagliosalmati poliuretano



- Guanto in filo continuo di fibra aramidica con spalmatura sul palmo in poliuretano.
- Ideale per la protezione delle mani contro oggetti taglienti e spigoli vivi.
- Settori di utilizzo: lavorazioni metalliche, manutenzione, falegnameria, vetreria, impiantisti, carrozzerie, officine meccaniche, manipolazione oggetti taglienti.
- Guanto morbido ed elastico, studiato appositamente per offrire il massimo comfort e protezione nelle lavorazioni.
- La completa assenza di cuciture nei punti di maggiore sforzo salvaguarda la pelle da eventuali irritazioni.

Code	Desc.	Measure
4460030540	32120-S	7/S
4460030545	32120-M	8/M
4460030550	32120-L	9/L
4460030555	32120-XL	10/XL

Coated cut-resistant gloves of polyurethane Plus



- Cut-resistant gloves made of Aramid fibre continuous filament, with polyurethane waterproof coating slip-resistant on the palm. Extremely cut-resistant (level 5, the highest possible).
- Suitable for hand protection from sharpened objects and sharp edges.
- Application sectors: metal processing, maintenance, joinery, glasshouses, installers, body shops, mechanical workshops, handling of sharp objects.
- Soft and elastic gloves, especially designed to offer the utmost comfort and protection during processing. The complete absence of seams in the points of maximum stress protects the skin from irritations.
- In compliance with CE cat. II.

Code	Desc.	Measure
4460001220	3947/7	S/7
4460001230	3947/8	M/8
4460001240	3947/9	L/9
4460001250	3947/10	XL/10

Cut resistant gloves latex



- Polyester cotton glove with latex coated palm.
- To be used to protect the operator from cutting elements, glass, foils.
- Intended Use: glaziers, window fitters, sheet metal, assembly.
- Benefits: ventilated back and wrist stretch.
- Treaty to protect the user from bacteria and microbes.
- Under EC CAT.II

Code	Desc.	Taglia
4460027355	32105/7	S
4460027360	32105/8	M
4460027365	32105/9	L
4460027370	32105/10	XL

Cut resistant gloves latex prevent



- Cotton gloves with latex coated palm.
- To be used to protect the operator from cutting elements, glass, foils.
- Intended Use: glaziers, windows, plumbing, assembly, construction, structural steel work.
- Benefits: ventilated back and wrist stretch.
- Reinforced between thumb and forefinger.
- Treaty to protect the user from bacteria and microbes.
- In accordance with CE cat. II.

Code	Desc.	Taglia
4460027390	32110/10	XL

Cotton gloves



- Cotton gloves continuous thread.
- Hemmed at the bottom.
- Extremely sensitive.
- Ideal for inspection, assembly lines and light work and clean.
- A CE cat. 1.

Code	Desc.	L mm	Taglia
4460007410	4018	230	8 - 9

Gloves antivibration



- Cotton gloves and nylon with anti-vibration coating. Perfect.
- Particularly suitable for the area of carpentry, the frame, plant, workshop and construction. For use with electric and pneumatic tools that emit strong vibrations, such as: hammer drills, hammers, sanders, impact wrenches.
- Palm coated by a special support chloroprene which absorbs effectively the vibrations to the hand.
- Comply with the requirements of EN ISO 10819: 1996 for the prevention of risks of exposure to hand-arm vibration.
- In accordance with CE - Cat. I.

Code	Desc.	Taglia
4460030480	32065/9	L

thermal gloves



- Gloves yarn acrylic-nylon and foam composite, without seams.
- Particularly suitable for working storage, shipping, hydraulic, assembly, building and in cold storage. Suitable for food contact
- Internally lined with elasticized wrist.
- Palm coated with a special compound foam with water-repellent treatment that ensures a perfect grip in both wet and dry conditions.
- Specially designed to withstand the cold and contact with objects at room temperature until -50 °. Able to prevent the spreading of heat from hands.
- In accordance with CE - Cat. I.

Code	Desc.	Taglia
4460030460	32045/8	M
4460030465	32045/9	L
4460030470	32045/10	XL
4460030475	32045/11	XXL

Nitrile gloves



- Excellent resistance against chemical and mechanical resistance.
- Exceptional flexibility '.
- Excellent resistance to abrasion and puncture.
- Great entry, plush lining.
- It contains fungicidal and bacteriostatic agent that preserves the hygiene of the hand.
- Ideal for chemical, automotive, machine shop, automotive, machining.
- In accordance with CE - Cat. III.

Code	Desc.	L mm	Taglia
4460008530	4200-M	330	8
4460008535	4200-L	330	9
4460008540	4200-XL	330	10

PVC gloves



- PVC coated glove.
- To be used to protect the operator from chemicals and microorganisms.
- Intended Use: mechanical, chemical, refineries, recycling, waste collection.
- Benefits: cotton lined interior.
- Antibacterial treatment.
- Waterproof.
- Excellent abrasion resistance.
- In accordance with CE cat. III.

Code	Desc.	L cm	Photo	Taglia
4460027400	31115	35	A	10 - XL
4460027410	31120	58	B	10 - XL

60 cm knurled rubber gloves



- Gloves of pure natural latex (rubber) with slip-resistant knurled palm and back, smooth inside, total length 60 cm, with antidrip hem.
- Indicated for the following working sectors: building and installation of ceramic, handling of slippery, sharp objects, sandblasting, dismantling of vehicles, waste collection.
- Featuring high mechanical strength and slip-resistant. Suitable for processing slippery parts and for cleaning extremely dirty and greasy material.
- Good shear and perforation strength, high elasticity of the material.

Code	Desc.	Taglia
4460042095	32370/10	XL


Nitrile gloves Standard Meccanocar



- Ambidextrous gloves nitrile disposable.
- Wholly nitrile, latex, with pulverization and internal light rough finish to allow a better grip of objects.
- Packed in practical dispenser 100 pieces.
- Quality Standard AQL 1.5.
- Complying with EN 455 1 and 2.



CE EN 455 1 & 2
AQL 1,5



Code	Desc.	Taglia	Leng. mm
4460021000	24000/M	8/M	240
4460021010	24000/L	9/L	240
4460021020	24000/XL	10/XL	240

Nitrile gloves standard powder



- Disposable glove SYNTHETIC NITRILE light blue, beaded ambidextrous, powder free.
- Indicated in all employment sectors, from mechanical industry, crafts. Suitable for contact with foods, and can be used in all areas of the food industry.
- High sensitivity, dexterity and comfort. Fingertips to non-slip palms. Chemical resistance to detergents and cleaners also concentrated, hydrocarbons, solvents, ethers and freon (TF). Good mechanical strength to the glove disposable latex / vinyl.
- Disposable multipurpose controlled quality AQL 1.5 (freedom from holes) for long-term use to protect the hand and / or the product handled. High biocompatibility (free from natural latex).
- Recommended for people allergic to latex.

Code	Desc.	Taglia
4460000370	8716-S	S/6-6,5
4460000375	8716-M	M/7-7,5
4460000380	8716-L	L/8-8,5
4460000385	8716-XL	XL/9-9,5

Guanti usa e getta in nitrile “Grease Monkey”



- Guanti in nitrile usa e getta dalla costruzione robusta e dalla resistenza altissima, dotati di un'ottima presa, una comodità ineguagliabile e, grazie alla completa assenza di lattice, assolutamente sicuri per le persone allergiche al contatto con tale materiale. Non contengono talco.
- Indicati per lavorazioni a contatto con superfici umide o oleose: assemblaggi e manutenzioni, autofficine, autocarrozzerie, carpenterie meccaniche, metalliche, costruzioni e montaggi di strutture metalliche. Conformi anche per l'utilizzo nel campo alimentare.
- Il tipo di nitrile utilizzato permette di avere alti spessori sia sul palmo sia sulle dita, mantenendo un'elevata flessibilità ed un grado di destrezza massimo, la superficie di dita, palmo e dorso con la speciale finitura in rilievo a squama di pesce permette una presa sicura sui materiali scivolosi, una leggera rugosità interna garantisce la migliore aderenza del guanto alla mano.
- Forniti in dispenser di cartone, dotati di bordino salvagoccia sul polsino. Indice AQL 1,5.

Code	Desc.	Taglia
4460000440	8718M	8 - M
4460000450	8718L	9 - L
4460000460	8718XL	10 - XL
4460000470	8718XXL	11 - XXL

Blacks nitrile gloves standard without powder



- Disposable glove SYNTHETIC NITRILE black, beaded ambidextrous, powder free. The special compound makes them very flexible and resistant to tearing.
- Indicated in all employment sectors, from mechanical industry, crafts and in the medical industry as non-sterile glove.
- High sensitivity, dexterity and comfort. Fingertips to non-slip palms. Chemical resistance to detergents and cleaners also concentrated, hydrocarbons, solvents, ethers and freon (TF). Good mechanical strength to the glove disposable latex / vinyl.
- Disposable multipurpose controlled quality AQL 1.5 (freedom from holes) for long-term use to protect the hand and / or the product handled. High biocompatibility (free from natural latex).
- Recommended for people allergic to latex.

Code	Desc.	Taglia
4460000140	7119-S	S/6-6,5
4460000150	7119-M	M/7-7,5
4460000160	7119-L	L/8-8,5
4460000170	7119-XL	XL/9-9,5

Nitrile gloves Plus Meccanocar



- Nitrile disposable gloves ambidextrous not pulverized.
- Wholly nitrile, latex, light rough finish to allow a better grip of objects.
- High resistance to oils, grease, hydrocarbons and some solvents.
- The thickness and the material used make the gloves extremely resistant and durable.
- Packaged in convenient dispenser of 50 pieces.
- Quality Standard AQL 1.5.
- Complying with EN 455 1 and 2.

Code	Desc.	Taglia	Leng. mm
4460021100	24100/M	8/M	240
4460021110	24100/L	9/L	240
4460021120	24100/XL	10/XL	240

Nitrile disposable gloves Ansell Touch N Tuff ®



- Nitrile ambidextrous.
- Treated with powdered version.
- Protection against chemical irritants.
- Ideal for workshops, body shops, fuel pumps.
- A CE cat. III.
- In accordance with EN 374.

Code	Desc.	L mm	Taglia
4460008570	4202-M	240	8
4460008575	4202-L	240	9
4460008577	4202-XL	240	10

Disposable vinyl gloves



- Vinyl gloves ambidextrous highly sensitive 'i'.
- Contain no talc to avoid contaminating the products.
- Inside treated with powdered version.
- Ideal for body shops, handling of Plexiglas, precision assembly, inspection work, suitable for the food industry, essential in the handling of paints, dyes, glues and resins
- Solvent resistant.
- A CE cat. III.

Code	Desc.	L mm	Taglia
4460007420	4019-L	235	8 - 8 1/2
4460007425	4019-XL	235	9 - 9 1/2

Latex gloves shimmed caql 1.5



- Protective gloves disposable latex rubber, high thickness and increased length for maximum protection from chemical and mechanical hazards. Dust free and treated for minimizing the risk of allergies.
- Suitable for use in body shops, machine shops, in the area of maintenance and professional cleaning, industrial processes, in contact with hydrocarbons and food.
- Roughened externally for a good grip, high durability and protection, high resistance to mechanical stress and hydrocarbons, acids and bases.
- Supplied in dispenser box of 50 pieces.

Code	Desc.	Taglia
4460031050	32355M	8
4460031055	32355L	9
4460031060	32355XL	10
4460031065	32355XXL	11

Standard latex gloves without powder



- Disposable glove of natural latex, milky white, beaded ambidextrous, powder free.
- Indicated in all employment sectors, from mechanical industry, crafts and in the medical industry as non-sterile glove. Suitable for contact with foods, and can be used in all areas of the food industry.
- High sensitivity, dexterity and comfort. Fingertips to non-slip palms. Chemical resistance to detergents and cleaners also concentrated acids and bases. Good mechanical strength and high elasticity.
- Disposable multipurpose controlled quality AQL 1.5 (freedom from holes) for long-term use to protect the hand and / or the product handled.

Code	Desc.	Taglia
4460000180	7120-S	S/6-6,5
4460000190	7120-M	M/7-7,5
4460000200	7120-L	L/8-8,5
4460000210	7120-XL	XL/9-9,5

Disposable latex gloves with talc



- Guanto monouso in lattice naturale, di colore bianco latte, ambidestro con bordino, trattato internamente con polvere di amido vegetale.
- Indicato in tutti i settori lavorativi, dalla meccanica all'industria, all'artigianato e nel settore medico come guanto non sterile. Idonei al contatto con alimenti, e utilizzabili in tutti i campi del settore alimentare.
- Elevata sensibilità, destrezza e comfort. Punta delle dita a superficie ruvida antiscivolo. Resistenza chimica a detersivi e detergenti anche concentrati, acidi e basi. Buona resistenza meccanica ed elevata elasticità.
- Monouso polivalente di qualità controllata AQL 1.5 (per assenza di fori) per utilizzi di lunga durata a protezione della mano e/o del prodotto manipolato.

Code	Desc.	Taglia
4460004790	3983-S	S/6-6,5
4460004795	3983-M	M/7-7,5
4460004800	3983-L	L/8-8,5
4460004810	3983-XL	XL/9-9,5