

Springlock releases for A / C systems



- Series of releases for specific fittings Springlock circuit of air conditioning for cars and trucks.
- Suitable for all workshops, car electricians, body shops who need to perform disassembly circuit for repairs and maintenance.
- Complete kit that allows removal without damage to the fittings used on many brands of vehicles.
- Content: release red pipe G6. release blue pipe G8. release black tube G10. release white tube G12.

Code	Desc.
4770004600	320

Device for disconnection fuel hoses and air conditioning



- Set of 6 tools to disconnect the quick-release devices that are mounted on the tubes of the air conditioning and the fuel pipes of all models of cars: Ford, Opel etc.
- The set includes the following sizes: 5/16" - 3/8" - 1/2" - 5/8" - 3/4" - 7/8".

Code	Desc.
4770001330	133

Quick coupler for high pressure R134a



- Quick connection with metal tap taken high pressure weather systems operating with gas R134a.
- Article indicated as replacement for all charging stations air conditioners.
- Thread connecting the pipes 1/4 sae threaded male or female M14.

Code	Desc.	Thread
4140400320	8019	Maschio 1/4 SAE
4140400340	8021	Femmina M14

Low pressure quick coupler for R134a



- Quick connection with metal tap took low-pressure weather systems operating with gas R134a.
- Article indicated as replacement for all charging stations air conditioners.
- Thread connecting the pipes 1/4 sae threaded male or female M14.

Code	Desc.	Thread
4140400330	8020	Maschio 1/4 SAE
4140400350	8022	Femmina M14

Quick Hitch special charging high pressure R134a



- Special quick coupling for high pressure side, which is essential to solve the problems during maintenance of existing space on the drive specified.
- Suitable for all workshops, car electricians, body shops who need to perform disassembly circuit for repairs and maintenance.
- The connector allows to easily and quickly extend the original attack of the machine charging, allowing to reach without disassembling other details the outlet of high pressure.

Code	Desc.	Application
4770004650	325	BMW serie 5 – Ford S Max – Ford Galaxy – Volvo S3 – Mercedes SLK

Quick Hitch special charging high pressure R134a



- Special quick coupling for high pressure side, which is essential to solve the problems during maintenance on the car described, on which there is no connection for low pressure.
- Suitable for all workshops, car electricians, body shops who need to perform disassembly circuit for repairs and maintenance.
- The connector allows to connect with the low pressure side of the machine to the charging circuit of the car, missing the origin of a specific attack, and recharge the circuit.

Code	Desc.	Applications
4770004660	326	Auto del gruppo PSA-Renault-Opel

7

High/low pressure quick couplings for R134a with protection



- Quick couplings for recharging stations of gas R134a, completely made of metal, reliable and safe. Equipped with tap and protection against impacts and crushing.
- Equipped with standard adapter that changes, at will, the threading from female M 14x1.5 to male 1/4 SAE for the utmost reliability.

Code	Desc.	Presi	Color
4140400390	8026	Low pressure	Blue
4140400400	8027	High pressure	Red

High/low pressure quick couplings for R1234yf with protection



- Quick couplings for recharging stations of gas R1234yf, completely made of metal, reliable and safe. Equipped with tap and protection against impacts and crushing.
- Equipped with standard female threading M 12x1.5.

Code	Desc.	Presa	Color
4140400410	8028	Low pressure	Blue
4140400420	8029	High pressure	Red

Adapters for high/low pressure quick couplings



- Adapters complete with seals, useful to transform the female fittings of quick couplings for air conditioning machine. Made of brass with O-rings suitable for cooling gas.
- They change the female threading M 12 x 1.5 in into male threading respectively 1/4 SAE or 3/8 SAE.

Code	Desc.	Thread
4140400430	8030	M12 > 1/4 SAE
4140400440	8031	M12 > 3/8SAE

Extension for low pressure recharge R1234yf



- Extension that can be mounted on the low pressure socket of the air conditioning systems charged with gas R1234yf and allows to work on all car models having the socket in sunken and hidden position, hardly accessible (e.g. Opel and Ford cars).
- Completely made in metal and equipped with the valve against the gas leaks.

Code	Desc.
4140400450	8032