

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 411 00 20450-6362
Product name: ENGINE CLEANER PETROL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Additive for cleaning petrol injection systems

1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.
Full address: Via San Francesco, 22
District and Country: 56033 Capannoli (PI)
Italy
Tel. +39 0587 609433
Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet: moreno.meini@meccanocar.it
Product distribution by:

1.4. Emergency telephone number

For urgent inquiries refer to: National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

ENGINE CLEANER PETROL

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P260	Do not breathe fume / mist / vapours.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER / doctor.

Contains:	TOLUENE HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC ISOBUTYL ALCOHOL ETHYL ACETATE
------------------	---

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
TOLUENE		

Meccanocar Italia S.r.l.	Revision nr. 5 Dated 19/07/2021
ENGINE CLEANER PETROL	Printed on 19/07/2021 Page n. 3/23 Replaced revision:4 (Dated: 17/02/2020)

CAS 108-88-3	$40 \leq x < 42,5$	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412
EC 203-625-9		
INDEX 601-021-00-3		
Reg. no. 01-2119471310-51-XXXX		
ISOBUTYL ALCOHOL		
CAS 78-83-1	$40 \leq x < 42,5$	Flam. Liq. 3 H226, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336
EC 201-148-0		
INDEX 603-108-00-1		
Reg. no. 01-2119484609-23-XXXX		
HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC		
CAS 64742-48-9	$13,5 \leq x < 15$	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
EC 919-857-5		
INDEX -		
Reg. no. 01-2119463258-33-XXXX		
ETHYL ACETATE		
CAS 141-78-6	$6 \leq x < 7$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 205-500-4		
INDEX 607-022-00-5		
Reg. no. 01-2119475103-46-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

ENGINE CLEANER PETROL**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

TOLUENE

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	192	50	384	100	SKIN		
VLEP	FRA	76,8	20	384	100	SKIN		
WEL	GBR	191	50	384	100	SKIN		
VLEP	ITA	192	50			SKIN		
TLV	NOR	94	25			SKIN		
VLE	PRT	192	50	384	100	SKIN		
OEL	EU	192	50	384	100	SKIN		
TLV-ACGIH		75,4	20					
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,68		mg/l		
Normal value in marine water				0,68		mg/l		
Normal value for fresh water sediment				16,39		mg/kg		
Normal value for marine water sediment				16,39		mg/kg		
Normal value of STP microorganisms				13,61		mg/l		
Normal value for the terrestrial compartment				2,89		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,13 mg/kg bw/d				
Inhalation	226 mg/m3	226 mg/m3	56,5 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg bw/d				384 mg/kg bw/d
ETHYL ACETATE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	734	200	1468	400			
VLEP	FRA	1400	400					
WEL	GBR	734	200	1468	400			
VLEP	ITA	734	200	1468	400			
TLV	NOR	734	200					
VLE	PRT	734	200	1468	400			
OEL	EU	734	200	1468	400			
TLV-ACGIH		1441	400					
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,24		mg/l		
Normal value in marine water				0,024		mg/l		
Normal value for fresh water sediment				1,15		mg/kg		
Normal value for marine water sediment				0,115		mg/kg		
Normal value of STP microorganisms				650		mg/l		

ENGINE CLEANER PETROL

Normal value for the food chain (secondary poisoning)				0,2	mg/kg			
Normal value for the terrestrial compartment				0,148	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin				37 mg/kg bw/d				63 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

ENGINE CLEANER PETROL

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

ISOBUTYL ALCOHOL

Suitable safety gloves resistant to chemicals (EN 374) also with prolonged direct contact (Recommended: protection index 6, corresponding to > 480 minutes of breakthrough time according to EN 374): Eg nitrile rubber (0.4 mm), chloroprene rubber (0.5mm), butyl rubber (0.7mm) etc.

The manufacturer's instructions for use must be observed due to the wide variety of types.

Additional note: specifications are based on tests, literature data and information from glove manufacturers or derive from similar substances by analogy. Due to many conditions (eg temperature), it should be considered that the practical use of a chemical protective glove in practice can be much shorter than the breakthrough time determined through testing.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Chemical resistant gloves are recommended. Nitrile, standards CEN EN 420 and EN 374 provide general requirements and lists of types of gloves.

ETHYL ACETATE

Butyl rubber gloves (opening times > 480 minutes), Neoprene TM rubber, nitrile rubber (opening times up to 480 minutes).

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	6 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,825
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	425 °C

ENGINE CLEANER PETROL

Decomposition temperature Not available

Viscosity Not available

Explosive properties Not available

Oxidising properties Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.

ETHYL ACETATE

It slowly decomposes to acetic acid and ethanol due to the action of light, air and water. Stable under normal conditions. Upon storage, it is slowly decomposed by water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ISOBUTYL ALCOHOL

Reacts with strong oxidizing agents

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals,hydrides,oleum.May react violently with: fluorine,strong oxidising agents,chlorosulphuric acid,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Avoid heat, sparks, open flames and other sources of ignition.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

Ignition sources.

10.5. Incompatible materials

ISOBUTYL ALCOHOL

Strong oxidizing agents

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Strong oxidants

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

Oxidizing agents, acids, alkalis.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYL ACETATE

Carbon oxides on combustion.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TOLUENE

ENGINE CLEANER PETROL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**TOLUENE**

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects**TOLUENE**

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

TOLUENE

LD50 (Oral) 5580 mg/kg Rat

LD50 (Dermal) 12124 mg/kg Rabbit

LC50 (Inhalation) 28,1 mg/l/4h Rat

ISOBUTYL ALCOHOL

Method: OECD 401

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: LD50> 2830 mg / kg bw

Method: OECD 402

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Inhalation

Results: LD50> 2000 mg / kg bw

Method: OECD 402

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: LD50> 2000 mg / kg bw

TOLUENE

Method: Equivalent or similar to EU Method B.1

Reliability: 2

Species: Rat (Sprague-Dawley Cobb; male)

ENGINE CLEANER PETROL

Route of exposure: Oral
Results: LD50 = 5580 mg / kg bw
Method: Equivalent or similar to OECD 403
Reliability: 2
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Inhalation (vapors)
Results: LC50 = 25.7 mg / L air
Method: Not indicated
Reliability: 2
Species: Rabbit
Route of exposure: Dermal
Results: LD50> 5000 mg / kg bw
Bibliographic reference: Range-finding toxicity data: List VII, Smyth HF, Carpenter CP, Weil CS, Pozzani UC, Streigel JA and Nycum JS (1969)

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 423
Reliability: 2
Species: Rat (Wistar; male / female)
Route of exposure: Oral
Results: LD50> 15 000 mg / kg bw
Method: Equivalent or similar to OECD 403
Reliability: 1
Species: Rat (Crj: CD (SD); male / female)
Route of exposure: Inhalation (vapors)
Results: LC50> 4 951 mg / m³ air
Method: Equivalent or similar to OECD 402
Reliability: 2
Species: Rabbit (New Zealand White; male / female)
Route of exposure: Dermal
Results: LD50> 5 000 mg / kg bw

ETHYL ACETATE

Method: Multi-Substance Rule for the Testing of Neurotoxicity 40 CFR Part 799 (58 FR 40262)
Reliability: 1
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative
Method: Not indicated
Reliability: 2
Species: Rabbit (New Zealand White; male)
Route of exposure: Dermal
Results: LD50> 20 000 mg / kg bw

SKIN CORROSION / IRRITATION

Causes skin irritation

TOLUENE

Method: EU Method B.4
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Irritating

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 404
Reliability: 1
Species: Rabbit (New Zealand White)

ENGINE CLEANER PETROL

Route of exposure: Dermal
Results: Irritating

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

ISOBUTYL ALCOHOL

Method: OECD 405
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Corrosive

TOLUENE

Method: OECD 405
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Slightly irritating

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 405
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

ETHYL ACETATE

Method: OECD 405
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

ISOBUTYL ALCOHOL

Method: QSAR
Reliability: 1
Species: Not indicated
Route of exposure: Dermal
Results: Not classified

TOLUENE

Method: EU Method B.6
Reliability: 1
Species: guinea pig (Himalayan Albino; female)
Route of exposure: Dermal
Results: Not sensitizing

ENGINE CLEANER PETROL

Skin sensitization

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 406

Reliability: 2

Species: guinea pig (Hartley; female)

Route of exposure: Dermal

Results: Not sensitizing

ETHYL ACETATE

Method: OECD 406

Reliability: 1

Species: guinea pig (Dunkin-Hartley; female)

Route of exposure: Dermal

Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

ISOBUTYL ALCOHOL

Method: Not indicated - in vitro test

Reliability: 2

Species: Chinese hamster

Results: Negative with and without metabolic activation

Bibliographic reference: Evaluation of the genotoxic potential of some microbial volatile organic compounds (MVOC) with the comet assay, the micronucleus assay and the HPRT gene mutation assay, Kreja L, Seidel H-J (2002)

Method: OECD 474-test in vivo

Reliability: 1

Species: Mouse (NMRI; male / female)

Route of exposure: Oral

Results: Negative

TOLUENE

Method: Equivalent or similar to EU Method B.13 / 14-in vitro test

Reliability: 2

Species: S. typhimurium

Results: Negative with and without metabolic activation

Method: Not indicated - in vivo test

Reliability: 2

Species: Rat

Route of exposure: Intraperitoneal

Results: Negative

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative with or without metabolic activation

Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 1

Species: Mouse (CD-1; male / female)

Route of exposure: Oral

Results: Negative

ETHYL ACETATE

ENGINE CLEANER PETROL

Method: Equivalent or similar to OECD 471 in vitro test
Reliability: 2
Species: S. typhimurium
Results: Negative with and without metabolic activation
Method: Equivalent or similar to OECD 474 in vivo test
Reliability: 2
Species: Chinese hamster (male / female)
Route of exposure: Oral
Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 453
Reliability: 1
Species: Rat (F344 / N; male / female)
Route of exposure: Inhalation (vapors)
Results: NOAEC 138 mg / m³ air

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

ETHYL ACETATE

Method: Equivalent or similar to OECD 416
Reliability: 1
Species: Mouse (CD-1; male / female)
Route of exposure: Oral
Results: Negative
Method: Equivalent or similar to OECD 414
Reliability: 2
Species: Rat (Sprague-Dawley)
Route of exposure: Inhalation
Results: Negative

Adverse effects on sexual function and fertility
ISOBUTYL ALCOHOL

Method: EPA OPPTS 870.3800
Reliability: 1
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative, NOAEL (fertility) > = 7.5 mg / L air

TOLUENE

Method: Not indicated
Reliability: 2
Species: Rat (Sprague_Dawley; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative, NOAEC (fertility) = 600 ppm

ENGINE CLEANER PETROL

Bibliographic reference: Reproductive and developmental toxicity studies of toluene II. Effects of inhalation exposure on fertility in rats, Ono A, Sekita K, Ogawa Y, Hirose A, Suzuki S, Saito M, Naito K, Kaneko T, Furuya T, Kawashima K, Yasuhara K, Matsumoto K, Tanaka S, Inoue T and Kurokawa Y (1996)

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD TG 413

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Inhalation (vapors)

Results: NOAEC > = 400 ppm

Adverse effects on development of the offspring

ISOBUTYL ALCOHOL

Method: OECD 414

Reliability: 1

Species: Rat (Wistar)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEL (development) = 10 mg / L air

TOLUENE

Method: Not indicated

Reliability: 2

Species: Rat (Wistar)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEC (development) = 600 ppm

Bibliographic reference: Postnatal development and behavior of Wistar rats after prenatal toluene exposure, Thiel R and Chahoud I (1997)

STOT - SINGLE EXPOSURE

May cause respiratory irritation

May cause drowsiness or dizziness

ISOBUTYL ALCOHOL

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

TOLUENE

Based on available data and through expert judgment, the substance is classified in the target prgani toxicity class for single exposure.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

ETHYL ACETATE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

Target organ

ISOBUTYL ALCOHOL

Respiratory tract

TOLUENE

ENGINE CLEANER PETROL

Central nervous system

ETHYL ACETATE

Central nervous system

Route of exposure
TOLUENE

Inhalation

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Dermal and inhalation

ETHYL ACETATE

Inhalation

STOT - REPEATED EXPOSURE

May cause damage to organs

ISOBUTYL ALCOHOL

Method: OECD 408

Reliability: 1

Species: Rat (Wistar; male / female)

Route of exposure: Oral

Results: Negative, NOAEL > 1450 mg / kg bw / day

Method: EPA OPPTS 870.3800

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEL = 7.5 mg / L air

TOLUENE

Method: Equivalent or similar to EU Method B.26

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Oral

Results: NOAEL = 625 mg / kg bw / day

Method: EU Method B.29

Reliability: 1

Species: Rat (F344 / N; male / female)

Route of exposure: Inhalation (vapors)

Results: NOAEC = 625 ppm

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 422

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL > = 1000 mg / kg / day

Method: Equivalent or similar to OECD 413

Reliability: 1

ENGINE CLEANER PETROL

Species: Rat (Albino; male / female)
Route of exposure: Inhalation (vapors)
Results: NOAEC 10186 mg / m³

ETHYL ACETATE

Method: Equivalent or similar to EPA OTS 795.2600
Reliability: 2
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Oral
Results: NOAEL 900 mg / kg bw / day
Method: EPA OTS 798.2450
Reliability: 1
Species: Rat (CrI: CD®BR; male / female)
Route of exposure: Inhalation
Results: LOEC 350 ppm

Target organ
TOLUENE

Neurological

Route of exposure
TOLUENE

Inhalation

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

TOLUENE

LC50 - for Fish	5,5 mg/l/96h
EC50 - for Crustacea	3,78 mg/l/48h
EC50 - for Algae / Aquatic Plants	134 mg/l/72h
EC10 for Algae / Aquatic Plants	10 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	10 mg/l

12.2. Persistence and degradability

ISOBUTYL ALCOHOL

Easily degradable in water, 70-80% in 28 days.

TOLUENE

Easily degradable in water.

ETHYL ACETATE

Rapidly degradable, 60% in 10 days.

ETHYL ACETATE

ENGINE CLEANER PETROL

Solubility in water > 10000 mg/l
Rapidly degradable

TOLUENE

Solubility in water 100 - 1000 mg/l
Rapidly degradable

ISOBUTYL ALCOHOL

Solubility in water 1000 - 10000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68
BCF 30

TOLUENE

Partition coefficient: n-octanol/water 2,73
BCF 90

ISOBUTYL ALCOHOL

Partition coefficient: n-octanol/water 1

12.4. Mobility in soil

ISOBUTYL ALCOHOL

Partition coefficient: soil/water 0,31

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

ISOBUTYL ALCOHOL

They must be disposed of or incinerated in accordance with local regulations.

ENGINE CLEANER PETROL

ETHYL ACETATE

Dispose of as hazardous waste. Recover or recycle if possible. Otherwise incineration. Dispose according to local regulations.

Disposal of the container: empty the container completely. Empty containers may contain highly flammable residues. Do not cut, grind, puncture, weld or dispose of containers unless adequate precautions have been taken against this hazard. Do not remove the container labels until they are cleaned. Send to drum recovery or metal recovery.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1993
IATA:

14.2. UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, N.O.S.
IMDG: FLAMMABLE LIQUID, N.O.S.
IATA: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3
IMDG: Class: 3 Label: 3
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, III
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30
Special Provision: -
IMDG: EMS: F-E, S-E
IATA: Cargo:

Limited
Quantities: 5
L

Tunnel
restriction
code: (D/E)

Limited
Quantities: 5
L
Maximum
quantity: 220

Packaging
instructions:

Meccanocar Italia S.r.l.	Revision nr. 5 Dated 19/07/2021
ENGINE CLEANER PETROL	Printed on 19/07/2021 Page n. 21/23 Replaced revision:4 (Dated: 17/02/2020)

Pass.:	L Maximum quantity: 60 L	366 Packaging instructions: 355
Special Instructions:	A3	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3 - 40

Contained substance

Point	48	TOLUENE Reg. no.: 01-2119471310-51- XXXX
-------	----	--

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

ENGINE CLEANER PETROL

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006

ENGINE CLEANER PETROL

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 09 / 11 / 15.