Revision nr. 1 Meccanocar Italia S.r.l. Dated 23/07/2020 First compilation Printed on 23/07/2020 **CALCIUM GREASE** Page n. 1/12

Safety Data Sheet According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

4	4	D==	44	:400	ntifier
1	1.1	Pro	anct	IGE	1titier

411 00 14830-2778 Code: Product name **CALCIUM GREASE**

1.2. Relevant identified uses of the substance or mixture and uses advised against Water repellent lubricating grease for boating Intended use

1.3. Details of the supplier of the safety data sheet

Meccanocar Italia S.r.l. Full address Via San Francesco, 22 District and Country 56033 Capannoli (PI)

Italy

Tel. +39 0587 609433 Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830. Hazard classification and indication:

2.2. Label elements

Hazard pictograms:

Signal words:

Hazard statements:

Precautionary statements:

Meccanocar Italia S.r.I. Revision nr. 1 Dated 23/07/2020 First compilation Printed on 23/07/2020 Page n. 2/12

--

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED.

SOLVENT, WAXED, HYDROGENATED

CAS 101316-72-7 $70 \le x < 74$ Carc. 1A H350, Classification note according to Annex VI to the CLP

Regulation: L

EC 309-877-7 INDEX -

Reg. no. 01-2119489969-06-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

Meccanocar Italia S.r.l.	Revision nr. 1
	Dated 23/07/2020
	First compilation
CALCIUM GREASE	Printed on 23/07/2020
	Page n. 3/12

UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Meccanocar Italia S.r.l.	Revision nr. 1 Dated 23/07/2020 First compilation
CALCIUM GREASE	Printed on 23/07/2020 Page n. 4/12

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED Predicted no-effect concentration - PNEC								
Normal value for the food of	chain (secondary poisor	ning)		9,33	m	g/kg		
Health - Derived no-ef	fect level - DNEL / [OMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,74 mg/kg bw/d				•
Inhalation							5,58 mg/m3	2,73 mg/m3
Skin								0,97 mg/kg bw/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

Meccanocar Italia S.r.l.	Revision nr. 1
	Dated 23/07/2020
	First compilation
CALCIUM GREASE	Printed on 23/07/2020
	Page n. 5/12

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liauid Colour Not available Odour characteristic Odour threshold Not available рН Not available Melting point / freezing point > 160 °C Initial boiling point Not available Boiling range Not available > 200 °C Flash point Evaporation rate Not available Flammability (solid, gas) Not available Not available Lower inflammability limit Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Not available Vapour pressure Vapour density Not available Relative density Not available Solubility insoluble in water Partition coefficient: n-octanol/water Not available > 300 °C Auto-ignition temperature Decomposition temperature Not available Not available Viscosity Explosive properties not explosive

9.2. Other information

Information not available

Oxidising properties

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

non oxidizing

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

Meccanocar Italia S.r.I. Revision nr. 1 Dated 23/07/2020 First compilation Printed on 23/07/2020 Page n. 6/12

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: Not classified (no significant component) LD50 (Dermal) of the mixture:

Not classified (no significant component)

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: OECD 401-Read across

Reliability: 1

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Oral

Results: LD50> 5000 mg / kg bw

Method: Equivalent or similar to OECD 403-Read across

Revision nr. 1

Dated 23/07/2020

First compilation

Printed on 23/07/2020
Page n. 7/12

CALCIUM GREASE

Reliability: 1

Species: Rat (Sprague-Dawley; male; female) Route of exposure: Inhalation (aerosol) Results: LC50 = 2.18 mg / L air Method: OECD 402-Read across

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal Results: LD50> 5000 mg / kg bw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Not indicated

Reliability: 2

Species: Rabbit (New Zealand White)

Route of exposure: Dermal Results: Not irritating

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 405-Read across

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular Results: Not irritating

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 406-Read across

Reliability: 1

Species: guinea pig (Hartley; male) Route of exposure: Dermal Results: Not sensitizing

. recaller rich content

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 471-Read across-test in vitro

Reliability: 1

Species: S. typhimurium

Results: Positive with metabolic activation Method: OECD 474-Read across-test in vivo

Reliability: 1

Species: Mouse (CD-1; male / female)

CALCIUM GREASE

Revision nr. 1

Dated 23/07/2020

First compilation

Printed on 23/07/2020

Page n. 8/12

Route of exposure: Oral

CARCINOGENICITY

Results: Negative

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 451-Read across

Reliability: 1

Species: Mouse (CF1; female) Route of exposure: Dermal

Results: Negative

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

LUBRICANT OILS (PETROLEUM), C24-50, ÉXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: OECD 421-Read across

Reliability: 1

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Oral

Results: Negative, NOAEL (fertility)> = 1000 mg / kg bw / day

Adverse effects on development of the offspring

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 414-Read across

Reliability: 1

Species: Rat (Sprague-Dawley)

Route of exposure: Dermal

Results: Positive, NOAEL (development) = 30 mg / kg bw / day

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 408

Reliability: 1

Species: Rat (Sprague-Dawley; male)

Route of exposure: Oral

Results: Negative, NOAEL = 125 mg / kg bw

Method: Equivalent or similar to OECD 412-Read across

Reliability: 2

Revision nr. 1

Dated 23/07/2020

First compilation

Printed on 23/07/2020

Page n. 9/12

CALCIUM GREASE

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Inhalation

Results: Negative, NOAEL = 200 mg / m3

Method: OECD 410-Read across

Reliability:

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal Results: NOEAL = 1000 mg / kg

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

12.1. Toxicity

Information not available

12.2. Persistence and degradability

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED Not easily degradable in water, from 2 to 4% in 28 days.

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

Meccanocar Italia S.r.I.	Revision nr. 1 Dated 23/07/2020
	First compilation
CALCIUM GREASE	Printed on 23/07/2020
O/LOIOM OILE/IOE	Page n. 10/12
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by	ov Road (ADR) and by Rail (RID), of
the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA)	regulations.
14.1. UN number	
Not applicable	
14.2. UN proper shipping name	
Not applicable	
14.3. Transport hazard class(es)	
Not applicable	
14.4. Packing group	
Not applicable	
14.5. Environmental hazards	
Not applicable	
14.6. Special precautions for user	
Not applicable	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Information not relevant	
SECTION 15. Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	

Seveso Category - Directive 2012/18/EC: None

Revision nr. 1

Dated 23/07/2020 First compilation

Printed on 23/07/2020

Page n. 11/12

CALCIUM GREASE

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point 28 LUBRICANT OILS

(PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED,

HYDROGENATED Reg. no.: 01-2119489969-06-XXXX

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 1A Carcinogenicity, category 1A

H350 May cause cancer.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)

Revision nr. 1 Meccanocar Italia S.r.l. Dated 23/07/2020 First compilation Printed on 23/07/2020 **CALCIUM GREASE** Page n. 12/12

- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 07 / 08 / 09 / 11 / 12 / 13 / 14 / 15 / 16.