ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 1/16

Replaced revision:2 (Dated: 08/01/2020)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 411 00 16550-4090

Product name ANTI SMELL SANITIZER (ONE SHOT)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Anti-mold sanitizer for closed environments

1.3. Details of the supplier of the safety data sheet

NameMeccanocar Italia S.r.I.Full addressVia San Francesco, 22District and Country56033 Capannoli (PI)

Italy

Tel. +39 0587 609433 Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Eye irritation, category 2 H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 2/16

Replaced revision:2 (Dated: 08/01/2020)





Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.

P211 Do not spray on an open flame or other ignition source.
P102 Keep out of reach of children

P260 Do not breathe the spray

P501 Dispose of contents/container in accordance with local dispositions

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

METHYL OXIDE DIMETHYLETER

CAS 115-10-6 62 \leq x < 66 Flam. Gas 1A H220, Press. Gas H280

EC 204-065-8

INDEX -

Reg. no. 01-2119472128-37-XXXX

PROPAN-2-OL

CAS 67-63-0 $35 \le x < 37.5$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7

INDEX 603-117-00-0

Reg. no. 01-2119457558-25-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 3/16

Replaced revision:2 (Dated: 08/01/2020)

health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 65,00 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 4/16

Replaced revision:2 (Dated: 08/01/2020)

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP España LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)

FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

EH40/2005 Workplace exposure limits (Third edition, published 2018) DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017 GBR United Kingdom ITA Italia

Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5 NOR Norge

TLV-ACGIH **ACGIH 2019**

METUVI OVIDE DIMETUVI ETED

Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLEP	ITA	983	400			INHAL	
Predicted no-effect concentration	n - PNEC						
Normal value in fresh water				1,55		mg/l	

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 5/16

Replaced revision:2 (Dated: 08/01/2020)

bw/d

Normal value in marine water	0,16	mg/l	_
Normal value for fresh water sediment	6,581	mg/kg	_
Normal value for marine water sediment	0,69	mg/kg	
Normal value for water, intermittent release	1,549	mg/l	_
Normal value for the terrestrial compartment	0,45	mg/kg	

Health - Derived no-effect	t level - DNEL / D	MEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation				471 mg/m3		NPI		1894 mg/m3

PROPAN-2-OL								
Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min		Remarks Observa		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	500	200	1000	400			
VLEP	FRA			980	400			
WEL	GBR	999	400	1250	500			
TLV	NOR	245	100					
TLV-ACGIH		492	200	983	400			
Predicted no-effect concen	tration - PNEC							
Normal value in fresh wate	r			140,9	m	g/l		
Normal value in marine water				140,9	m	g/l		
Normal value for fresh water sediment			552	m	g/kg			
Normal value for marine water sediment				552	m	mg/kg		
Normal value of STP microorganisms				2251	mg/l			
Normal value for the food chain (secondary poisoning)				160	mg/kg			
Normal value for the terrestrial compartment				28	mg/kg			
Health - Derived no-ef	fect level - DNEL / I	DMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				26 mg/kg bw/d		•		•
Inhalation				89 mg/m3				500 mg/m3
Skin				319 mg/kg				888 mg/kg

Legend:

DDODAN O O

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

bw/d

When choosing personal protective equipment, ask your chemical substance supplier for advice.

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020 Printed on 30/01/2020

Page n. 6/16

Replaced revision:2 (Dated: 08/01/2020)

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

PROPAN-2-OL

Respiratory protection: personal respiratory protection devices are normally not required. In inadequately ventilated areas, where workplace limits are exceeded, where there are unpleasant odors or where aerosols are present or smoke and fog occur, use a self-contained breathing apparatus or self-contained breathing apparatus with a type A filter or an appropriate combined filter, in compliance with EN 141.

Hand protection: the choice of an appropriate glove depends not only on its material but also on other quality characteristics and is different from one manufacturer to another. Observe the permeability and breakthrough time instructions provided by the glove supplier. Also take into consideration the specific local conditions in which the product is used, such as the danger of cuts, abrasions and contact times., Keep in mind that in daily use the durability of a chemical resistant protective glove can be considerably less than breakthrough time measured according to EN 374.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance aerosol Colour colourless Odour simile alla frutta Odour threshold Not available рH Not available Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point Not available Evaporation rate Not available Flammability (solid, gas) Not available Lower inflammability limit 2 % (V/V) Upper inflammability limit 26,2 % (V/V)

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020
Printed on 30/01/2020

Page n. 7/16

Replaced revision:2 (Dated: 08/01/2020)

Lower explosive limitNot availableUpper explosive limitNot availableVapour pressure4000 hPaVapour densityNot available

Relative density 1,26

Solubility partially soluble in water

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

Not available

Explosive properties

Not available

Oxidising properties

Not available

9.2. Other information

VOC (Directive 2010/75/EC): 99,50 % - 707,70 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

METHYL OXIDE DIMETHYLETER

Vapors can form an explosive mixture with air.

PROPAN-2-OL

Vapors can form an explosive mixture with air.

10.4. Conditions to avoid

Avoid overheating.

METHYL OXIDE DIMETHYLETER

Temperature:> 52 ° C

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 8/16

Replaced revision:2 (Dated: 08/01/2020)

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

METHYL OXIDE DIMETHYLETER

Oxygen, oxidizing agents, acid anhydrides, strong acids, carbon monoxide, acetic anhydride, powdered metals.

10.6. Hazardous decomposition products

METHYL OXIDE DIMETHYLETER

Formaldehyde, carbon dioxide (CO2), carbon monoxide, methanol.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:
Not classified (no significant component)
LD50 (Oral) of the mixture:
Not classified (no significant component)
LD50 (Dermal) of the mixture:
Not classified (no significant component)

PROPAN-2-OL

LD50 (Oral) 4710 mg/kg Rat

LD50 (Dermal) 12800 mg/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 9/16

Replaced revision:2 (Dated: 08/01/2020)

METHYL OXIDE DIMETHYLETER

LC50 (Inhalation) 164000 ppm/4h rat

METHYL OXIDE DIMETHYLETER

Method: Not indicated

Reliability: 2

Species: Rat (albino ChR-CD; male) Route of exposure: Inhalation (gas) Results: LC50: 164 000 ppm

PROPAN-2-OL

Method: Equivalent or similar to OECD 401

Reliability: 2

Species: Rat (Sherman) Route of exposure: Oral

Results: LD50: 5.84 other: g / kg body weight

Bibliographic reference: Smyth HF & Carpenter CP, FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY

LABORATORY (1948)

Method: Equivalent or similar to OECD 403

Reliability: 1 Species: Rat (Fischer 344; male / female) Route of exposure: Inhalation (vapor)

Results: LC50: ca. 5,000 ppm

Method: Equivalent or similar to OECD 402

Reliability: 2 Species: Rabbit

Route of exposure: Dermal Results: LD50: 16.4 mL / kg bw

Bibliographic reference: Smyth HF & Carpenter CP, FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY

LABORATORY (1948)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

PROPAN-2-OL

Method: Not indicated Reliability: 2 Species: Rabbit

Route of exposure: Dermal Results: Not classified

Bibliographic reference: Nixon G, Tyson C & Wertz W, Interspecies Comparisons of Skin Irritancy (1975)

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

PROPAN-2-OL

Method: Equivalent or similar to OECD 405

Reliability: 1

Species: Rabbit (New Zealand White)

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 10/16

Replaced revision:2 (Dated: 08/01/2020)

Route of exposure: Ocular Results: Category 2

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

PROPAN-2-OL

Method: OECD 406 Reliability: 1

Species: guinea pig (Hartley; male / female)

Route of exposure: Dermal Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative

Method: Equivalent or similar to OECD 477 in vivo test

Reliability: 2

Species: Drosophila melanogaster (male) Route of exposure: Inhalation (gas)

Results: Negative

PROPAN-2-OL

Method: Equivalent or similar to OECD 476 in vitro test

Reliability: 1
Species: Chinese hamster

Results: Negative with or without metabolic activation

Bibliographic reference:

Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 2

Species: Mouse (ICR; male / female)

Route of exposure: Oral Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 453

Reliability: 1

Species: Rat (CD (R) (SD) BR; male / female) Route of exposure: Inhalation (vapors)

Results: Negative

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 11/16

Replaced revision:2 (Dated: 08/01/2020)

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 452 Reliability: 1 Species: Rat (CD (SD) BR; male / female) Route of exposure: Inhalation (vapors)

Results: Negative

PROPAN-2-OL

Method: Equivalent or similar to OECD 416

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral Results: NOAEL 500

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

METHYL OXIDE DIMETHYLETER

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

PROPAN-2-OL

Based on the available data, the substance may cause damage to organs through single exposure and is therefore classified in this hazard class.

Route of exposure

PROPAN-2-OL

Inhalation.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

PROPAN-2-OL

Based on the available data and through expert judgment, the substance is not classified in the target organ hazard class for prolonged or repeated exposure.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

ANTI SMELL SANITIZER (ONE SHOT)

4400 mg/l

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 12/16

Replaced revision:2 (Dated: 08/01/2020)

SECTION 12. Ecological information

12.1. Toxicity

METHYL OXIDE DIMETHYLETER

 LC50 - for Fish
 4100 mg/l/96h

 EC50 - for Crustacea
 4400 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 154,917 mg/l/72h

 Chronic NOEC for Fish
 4100 mg/l

12.2. Persistence and degradability

Chronic NOEC for Crustacea

PROPAN-2-OL

Quickly degradable in water.

PROPAN-2-OL Rapidly degradable

METHYL OXIDE DIMETHYLETER

Solubility in water 45600 mg/l

12.3. Bioaccumulative potential

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

METHYL OXIDE DIMETHYLETER

Partition coefficient: n-octanol/water 0,07 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 13/16

Replaced revision:2 (Dated: 08/01/2020)

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

METHYL OXIDE DIMETHYLETER

It can be used after reconditioning. In accordance with local and national regulations. It must be incinerated in a suitable incineration plant in possession of an authorization issued by the competent authorities.

PROPAN-2-OL

After pre-treatment and compliance with the regulations for hazardous waste, they must be taken to a permitted hazardous waste landfill or a hazardous waste incinerator.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG,

1950

IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG,

IATA:

14.5. Environmental hazards

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 14/16

Replaced revision:2 (Dated: 08/01/2020)

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: -- Limited Quantities: 1

Tunnel restriction code: (D)

Special Provision: -EMS: F-D, S-U

Limited

Quantities: 1

Cargo:

Maximum quantity: 150

Packaging instructions: 203

Pass.:

Kg Maximum quantity: 75

Packaging instructions: 203

Special Instructions:

Kg A145, A167,

A802

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

IMDG:

IATA:

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

40 Point

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 15/16

Replaced revision:2 (Dated: 08/01/2020)

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A Flammable gas, category 1A

Aerosol 1 Aerosol, category 1
Aerosol 3 Aerosol, category 3

Flam. Liq. 2 Flammable liquid, category 2

Press. Gas Pressurised gas

Eye Irrit. 2 Eye irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H220 Extremely flammable gas.H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train

ANTI SMELL SANITIZER (ONE SHOT)

Revision nr. 3

Dated 27/01/2020

Printed on 30/01/2020

Page n. 16/16

Replaced revision:2 (Dated: 08/01/2020)

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 10 / 11 / 12 / 13 / 16.