

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **411 00 19200-5835**
Product name: **BLACK SPRAY CONTROL**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Sanding control paint**

1.3. Details of the supplier of the safety data sheet

Name: **Meccanocar Italia S.r.l.**
Full address: **Via San Francesco, 22**
District and Country: **56033 Capannoli (PI)**
Italy

Tel. **+39 0587 609433**

Fax **+39 0587 607145**

e-mail address of the competent person

responsible for the Safety Data Sheet: **moreno.meini@meccanocar.it**

1.4. Emergency telephone number

For urgent inquiries refer to: **National Poisons Information Service: +44 121 507 4123**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

BLACK SPRAY CONTROL

Signal words:

Danger

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P280 Wear eye protection / face protection.

Contains: ACETONE
 N-BUTYL ACETATE
 2-METHOXY-1-METHYLETHYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
ACETONE		
CAS 67-64-1	27 ≤ x < 28,5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
INDEX 606-001-00-8		
Reg. no. 01-2119471330-49-XXXX		
METHYL OXIDE DIMETHYLETER		
CAS 115-10-6	18 ≤ x < 19,5	Flam. Gas 1A H220, Press. Gas H280
EC 204-065-8		
INDEX -		
Reg. no. 01-2119472128-37-XXXX		

BLACK SPRAY CONTROL

PROPANE

CAS 74-98-6 $10,5 \leq x < 12$ Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U

EC 200-827-9

INDEX 601-003-00-5

Reg. no. 01-2119486944-21-XXXX

N-BUTYL ACETATE

CAS 123-86-4 $10,5 \leq x < 12$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

INDEX 607-025-00-1

Reg. no. 01-2119485493-29-XXXX

BUTANE

CAS 106-97-8 $9 \leq x < 10,5$ Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U

EC 203-448-7

INDEX 601-004-00-0

Reg. no. 01-2119474691-32-XXXX

2-METHOXY-1-METHYLETHYL ACETATE

CAS 108-65-6 $9 \leq x < 10,5$ Flam. Liq. 3 H226, STOT SE 3 H336

EC 203-603-9

INDEX 607-195-00-7

Reg. no. 01-2119475791-29-XXXX

NITROCELLULOSE

CAS 9004-70-0 $4 \leq x < 4,5$ Expl. 1.1 H201, Classification note according to Annex VI to the CLP Regulation: T

EC -

INDEX 603-037-00-6

ISOBUTANE

CAS 75-28-5 $4 \leq x < 4,5$ Flam. Gas 1A H220, Press. Gas H280

EC 200-857-2

INDEX 601-004-00-0

Reg. no. 01-2119485395-27-XXXX

XYLENE (MIXTURE OF ISOMERS)

CAS 1330-20-7 $2 \leq x < 2,5$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C

EC 215-535-7

INDEX 601-022-00-9

Reg. no. 01-2119488216-32-XXXX

ETHANOL

CAS 64-17-5 $2 \leq x < 2,5$ Flam. Liq. 2 H225, Eye Irrit. 2 H319

EC 200-578-6

INDEX 603-002-00-5

Reg. no. 01-2119457610-43-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 43,50 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

BLACK SPRAY CONTROL**6.2. Environmental precautions**

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

ACETONE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLEP	FRA	1210	500	2420	1000	
WEL	GBR	1210	500	3620	1500	

BLACK SPRAY CONTROL

VLEP	ITA	1210	500		
TLV	NOR	295	125		
VLE	PRT	1210	500		
OEL	EU	1210	500		
TLV-ACGIH			250	500	

Predicted no-effect concentration - PNEC					
Normal value in fresh water				10,6	mg/l
Normal value in marine water				1,06	mg/l
Normal value for fresh water sediment				30,4	mg/kg
Normal value for marine water sediment				3,04	mg/kg
Normal value of STP microorganisms				100	mg/l
Normal value for the terrestrial compartment				29,5	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				62 mg/kg bw/d				
Inhalation				200 mg/m3			2420 mg/m3	1210 mg/m3
Skin				62 mg/kg bw/d				186 mg/kg bw/d

METHYL OXIDE DIMETHYLETER
Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
VLEP	ITA	983	400	INHAL

Predicted no-effect concentration - PNEC					
Normal value in fresh water				1,55	mg/l
Normal value in marine water				0,16	mg/l
Normal value for fresh water sediment				6,581	mg/kg
Normal value for marine water sediment				0,69	mg/kg
Normal value for water, intermittent release				1,549	mg/l
Normal value for the terrestrial compartment				0,45	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				471 mg/m3		NPI		1894 mg/m3

N-BUTYL ACETATE
Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
VLA	ESP	724	150	965 200
VLEP	FRA	710	150	940 200
WEL	GBR	724	150	966 200

BLACK SPRAY CONTROL

Oral	500 mg/kg bw/d	systemic	36 mg/kg bw/d	systemic	systemic
Inhalation	33 mg/m3	33 mg/m3	550 mg/m3	275 mg/m3	
Skin		320 mg/kg bw/d		796 mg/kg bw/d	

BUTANE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
WEL	GBR	1450	600	1810	750	
TLV	NOR	600	250			
TLV-ACGIH					1000	

ETHANOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP			1910	1000	
VLEP	FRA	1900	1000	9500	5000	
WEL	GBR	1920	1000			
TLV	NOR	950	500			
TLV-ACGIH				1884	1000	
Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,96	mg/l	
Normal value in marine water				0,79	mg/l	
Normal value for fresh water sediment				3,6	mg/kg	
Normal value for marine water sediment				2,9	mg/kg	
Normal value of STP microorganisms				580	mg/l	
Normal value for the food chain (secondary poisoning)				0,38	mg/kg	
Normal value for the terrestrial compartment				0,63	mg/kg	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				87 mg/kg bw/d				
Inhalation				114 mg/m3				950 mg/m3
Skin				206 mg/kg bw/d				343 mg/kg bw/d

XYLENE (MIXTURE OF ISOMERS)**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	221	50	442	100	SKIN

BLACK SPRAY CONTROL

VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TLV	NOR	108	25			SKIN
VLE	PRT	221	50	442	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,327	mg/l	
Normal value in marine water				0,327	mg/l	
Normal value for fresh water sediment				12,46	mg/kg	
Normal value for marine water sediment				12,46	mg/kg	
Normal value of STP microorganisms				6,58	mg/l	
Normal value for the terrestrial compartment				2,31	mg/kg	

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				12,5 mg/kg bw/d				
Inhalation	260 mg/m3	260 mg/m3	65,3 mg/m3	65,3 mg/m3	442 mg/m3	442 mg/m3	221 mg/m3	221 mg/m3
Skin				125 mg/kg bw/d				212 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

BLACK SPRAY CONTROL

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

ACETONE

Protective gloves according to EN 374.

Glove material: Butyl rubber (butyl rubber) - Layer thickness > = 0.5 mm.

Breakthrough time: > 480 min.

Observe the glove manufacturer's instructions regarding penetrability and breakthrough time.

N-BUTYL ACETATE

Wear protective gloves. The recommendations are listed below. Other protective material can be used, depending on the situation, if adequate data on degradation and permeation are available. If other chemicals are used together with this chemical, the selection of materials should be based on the protection of all chemicals present.

2-METHOXY-1-METHYLETHYL ACETATE

Use gloves chemically resistant to this material in case of prolonged or frequent repeated contact. Use chemical resistant gloves classified according to EN374: protective gloves against chemicals and microorganisms. Examples of preferred barrier material for gloves include: Butyl rubber. Polyethylene. Chlorinated polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable barrier materials for gloves include: Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Nitrile / butadiene rubber ("nitrile" or "NBR"). In the event of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN 374). When only a short contact is expected, a glove with a protection class of 1 or more is recommended (breakthrough time greater than 10 minutes according to EN 374)

ISOBUTANE

Suitable glove material protective gloves, e.g. nitrile butadiene rubber gloves (NBR), leather gloves, heat insulating Selection of protective gloves to meet specific workplace requirements.

Suitability for specific workplaces must be clarified with the manufacturers of protective gloves.

The information is based on our tests, references from literature and information from glove manufacturers or derived by analogy with similar materials.

Remember that the useful time per day of a chemical protection glove can be much shorter than the breakthrough time determined according to EN 374 due to the numerous influencing factors involved.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Colour	black
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available

BLACK SPRAY CONTROL

Boiling range	Not available
Flash point	Not available
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	1,2 % (V/V)
Upper inflammability limit	18,6 % (V/V)
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	8300 hPa
Vapour density	Not available
Relative density	0,85
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE

Decomposes under the effect of heat.

Acetone reacts in the presence of bases. The vapor forms potentially explosive mixtures with the air. Heavier than air, they proceed at floor level and can flash at a great distance when turned on. It can electrostatically charge.

N-BUTYL ACETATE

Decomposes on contact with: water.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

NITROCELLULOSE

Avoid exposure to: heat,naked flames.Avoid contact with: strong oxidants.Fire hazard.Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

METHYL OXIDE DIMETHYLETER

Vapors can form an explosive mixture with air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

Vapors can form an explosive mixture with air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances,strong acids,alkaline metals.

BUTANE

Vapors can form an explosive mixture with air.

ISOBUTANE

Vapors can form an explosive mixture with air.

NITROCELLULOSE

Avoid exposure to: heat,shocks.Possibility of explosion.

ETHANOL

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl

BLACK SPRAY CONTROL

chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating.

ACETONE

Avoid exposure to: sources of heat,naked flames.

Highly flammable. Concentrated vapors are heavier than air. Forms explosive mixtures with air, even in empty and uncleaned containers. It can produce, if mixed with chlorinated hydrocarbons and exposed to light, highly irritating chlorine acetone.

METHYL OXIDE DIMETHYLETER

Temperature:> 52 ° C

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

Avoid contact with heat, sparks, open flames and static discharge. Avoid any source of ignition.

2-METHOXY-1-METHYLETHYL ACETATE

The product can oxidize at high temperatures. Avoid static discharge. Flammable vapors can be released at high temperatures

BUTANE

Avoid heat and sources of ignition.

ISOBUTANE

Keep away from heat and other causes of fire.

ETHANOL

Avoid exposure to: sources of heat, naked flames.

High temperatures. Proximity to sources of ignition

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE

BLACK SPRAY CONTROL

Incompatible with: acids, oxidising substances.

Attacks many plastics and rubbers. Condensation may form on contact with barium hydroxide, sodium hydroxide and many other alkaline materials. Avoid contact with strong oxidizing agents, alkalis and amines.

METHYL OXIDE DIMETHYLETER

Oxygen, oxidizing agents, acid anhydrides, strong acids, carbon monoxide, acetic anhydride, powdered metals.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

Strong acids and strong bases, strong oxidizing agents.

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

Avoid contact with oxidizing materials. Avoid contact with: strong acids. Strong oxidants.

BUTANE

Strong oxidizing agents, chlorine, oxygen.

ISOBUTANE

Strong oxidizing agents, chlorine, oxygen.

ETHANOL

strong mineral acids, oxidizing agents. Aluminum at higher temperatures.

10.6. Hazardous decomposition products**ACETONE**

May develop: ketenes, irritant substances.

In case of fire the following can be released: carbon monoxide and carbon dioxide.

METHYL OXIDE DIMETHYLETER

Formaldehyde, carbon dioxide (CO₂), carbon monoxide, methanol.

BUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO₂).

ISOBUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO₂).

NITROCELLULOSE

May develop: nitric oxide.

ETHANOL

Combustion will generate carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information**2-METHOXY-1-METHYLETHYL ACETATE**

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure**N-BUTYL ACETATE**

WORKERS: inhalation; contact with the skin.

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**N-BUTYL ACETATE**

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

BLACK SPRAY CONTROL**2-METHOXY-1-METHYLETHYL ACETATE**

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects**N-BUTYL ACETATE**

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

>2000 mg/kg

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral) 8530 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rat

ETHANOL

LD50 (Oral) > 5000 mg/kg Rat

LC50 (Inhalation) 120 mg/l/4h Pimephales promelas

NITROCELLULOSE

LD50 (Oral) > 5000 mg/kg Rat

BLACK SPRAY CONTROL**METHYL OXIDE DIMETHYLETER**

LC50 (Inhalation) 164000 ppm/4h rat

ACETONE

Method: Not indicated

Reliability: 2

Species: Rat (Sprague-Dawley)

Route of exposure: Oral

Results: LD50 = 5800 mg / kg bw

Bibliographic reference: Acetone potentiation of acute acetonitrile toxicity, Freeman JJ, Hayes EP (1985)

METHYL OXIDE DIMETHYLETER

Method: Not indicated

Reliability: 2

Species: Rat (albino ChR-CD; male)

Route of exposure: Inhalation (gas)

Results: LC50: 164 000 ppm

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 423

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: LD50 = 12.2 mL / kg bw

Method: Equivalent or similar to OECD 402

Reliability: 2

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: LD50> 16 mL / kg bw

PROPANE

Method: To study the concentrations at which the effects of the CNS occur following exposure by inhalation to propane by measuring LC50 (15 min) and EC50 (CNS) (10 min) in rats.

Reliability: 2

Species: Rat (Alderley Park (SPF); male / female)

Route of exposure: Inhalation

Results: LC50> 800 000 ppm

BUTANE

Method: Not indicated

Reliability: 2

Species: Rat (Alderley Park (SPF); male / female)

Route of exposure: Inhalation

Results: LC50: 1 443 mg / L air

XYLENE (MIXTURE OF ISOMERS)

Method: Equivalent or similar to EU Method B.1

Reliability: 1

Species: Rat (F344 / N; male / female)

BLACK SPRAY CONTROL

Route of exposure: Oral
Results: LD50 = 3523 mg / kg bw
Method: Equivalent or similar to EU Method B.2
Reliability: 2
Species: Rat (male)
Route of exposure: Inhalation (vapors)
Results: LD50 = 6700 ppm

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 404
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Not irritating

2-METHOXY-1-METHYLETHYL ACETATE

Method: Equivalent or similar from OECD 404
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Not irritating

ETHANOL

Method: OECD 404
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Not irritating

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

N-BUTYL ACETATE

Method: OECD 405
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

2-METHOXY-1-METHYLETHYL ACETATE

Method: Equivalent or similar from OECD 405
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

BLACK SPRAY CONTROL**ACETONE**

Method: Not indicated

Reliability: 2

Species: guinea pig (Hartley; female)

Route of exposure: Dermal

Results: Not sensitizing

Bibliographic reference: A new protocol and criteria for quantitative determination of sensitization potencies of chemicals by guinea pig maximization test, Nakamura A, Momma J, Sekiguchi H, Noda T, Yamano T, Kaniwa MA, Kojima S, Tsuda M, Kurokawa Y (1994)

Skin sensitization

2-METHOXY-1-METHYLETHYL ACETATE

Method: Equivalent or similar from OECD 406

Reliability: 2

Species: guinea pig (Dunkin-Hartley; male / female)

Route of exposure: Dermal

Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative

Method: Equivalent or similar to OECD 477 in vivo test

Reliability: 2

Species: Drosophila melanogaster (male)

Route of exposure: Inhalation (gas)

Results: Negative

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 471 in vitro test

Reliability: 2

Species: S. typhimurium, E. Coli

Results: Negative with and without metabolic activation

Method: OECD 474-test in vivo

Reliability: 2

Species: Mouse (NMRI; male / female)

Route of exposure: Oral

Results: Negative

PROPANE

Method: OECD 471 in vitro test

Reliability: 1

Species: Histidine Salmonella

Results: Negative with or without metabolic activation

Method: OECD 474-test in vivo

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation (gas)

Results: Negative

BLACK SPRAY CONTROL**2-METHOXY-1-METHYLETHYL ACETATE**

Method: Equivalent or similar from OECD 471-in vitro test

Reliability: 1

Species: Salmonella typhimurium

Results: Negative

BUTANE

Method: OECD 471 in vitro test

Reliability: 1

Species: Salmonella strains, S. typhimurium

Results: Negative without metabolic activation

Method: OECD 474-test in vivo

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation (gas)

Results: Negative

ETHANOL

Method: Equivalent or similar to OECD 478 in vivo test

Reliability: 2

Species: Mouse (CFLP and Alderley Park; male)

Route of exposure: Oral

Results: Negative

XYLENE (MIXTURE OF ISOMERS)

Method: Equivalent or similar to EU Method B.10-in vitro test

Reliability: 2

Species: Chinese hamster

Results: Negative with and without metabolic activation

Method: Equivalent or similar to OECD 478

Reliability: 2

Species: Mouse (Swiss Webster; male / female)

Route of exposure: Dermal

Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ACETONE

Method: Not indicated

Reliability: 2

Species: Mouse (ICR; female)

Route of exposure: Dermal

Results: Negative

Bibliographic reference: Mouse skin carcinogenicity tests of the flame retardants tris (2,3-dibromopropyl) phosphate, tetrakis (hydroxymethyl) phosphonium chloride, and polyvinyl bromide, Van Duuren BL, Loewengart G, Seldman I, Smith AC, Melchionne S (1974)

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 453

Reliability: 1

Species: Rat (CD (R) (SD) BR; male / female)

Route of exposure: Inhalation (vapors)

BLACK SPRAY CONTROL

Results: Negative

2-METHOXY-1-METHYLETHYL ACETATE

Method: OECD Guideline 453

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Inhalation (vapors)

Results: NOEL 300 ppm

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 452

Reliability: 1

Species: Rat (CD (SD) BR; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative

BUTANE

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation

Results: NOAEC 10000 ppm

Adverse effects on sexual function and fertility

N-BUTYL ACETATE

Method: OECD 416

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEC (fertility) = 750 ppm

PROPANE

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation

Results: NOAEC (fertility) 10 000 ppm

2-METHOXY-1-METHYLETHYL ACETATE

Method: OECD Guideline 416

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (vapors)

Results: NOAEL 300 ppm

BLACK SPRAY CONTROL**XYLENE (MIXTURE OF ISOMERS)**

Method: Not indicated

Reliability: 2

Species: Rat (CrI-CD® (SC) BR; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEC (fertility) = 500 ppm

Adverse effects on development of the offspring

ACETONE

Method: Equivalent or similar to OECD 414

Reliability: 1

Species: Rat (Sprague-Dawley)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEC (development) = 2200 ppm

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 414

Reliability: 1

Species: Rat (Sprague-Dawley)

Route of exposure: Inhalation (vapors)

Results: Positive, NOAEC (development) = 1500 ppm

PROPANE

Method: EPA OPPTS 870.3700

Reliability: 1

Species: Rat (VAF / Plus®, Sprague-Dawley Derived (CD®) CrI: CD® IGS BR)

Route of exposure: Inhalation (gas)

Results: NOAEC (development) 10 426 ppm

2-METHOXY-1-METHYLETHYL ACETATE

Method: Equivalent or similar from OECD 414

Reliability: 1

Species: Rat (Sprague-Dawley)

Route of exposure: Inhalation

Results: NOAEL 500 ppm

ETHANOL

Method: Not indicated

Reliability: 2

Species: Rat (Sprague-Dawley)

Route of exposure: Oral

Results: NOAEL (development) 5.2 g ethanol / kg bw / day

Bibliographic reference: Prenatal ethanol exposure has differential effects on fetal growth and skeletal ossification, Simpson ME, Duggal S, & Keiver K (2005)

XYLENE (MIXTURE OF ISOMERS)

Method: Equivalent or similar to OECD 414

Reliability: 2

Species: Rat (Sprague-Dawley)

Route of exposure: Inhalation (vapors)

Results: Negative (development)

BLACK SPRAY CONTROLSTOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

ACETONE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

METHYL OXIDE DIMETHYLETER

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

N-BUTYL ACETATE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

PROPANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

2-METHOXY-1-METHYLETHYL ACETATE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

BUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

ISOBUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

ETHANOL

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

XYLENE (MIXTURE OF ISOMERS)

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

Target organ

ACETONE

Narcotic effects

N-BUTYL ACETATE

Central nervous system.

2-METHOXY-1-METHYLETHYL ACETATE

Central nervous system

Route of exposure

BLACK SPRAY CONTROL

ACETONE

Inhalation

2-METHOXY-1-METHYLETHYL ACETATE

Oral

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ACETONE

Method: Equivalent or similar to OECD 408

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Oral

Results: Negative, NOAEL = 10000 ppm

Method: Not indicated

Reliability: 2

Species: Rat (Sprague-Dawley; male)

Route of exposure: Inhalation

Results: Negative, NOAEC = 19000 ppm

Bibliographic reference: Evaluation of toluene and acetone inhalant abuse. II. Model development and toxicology, Bruckner JV, Peterson RG (1981)

Method: Not indicated

Reliability: 2

Species: Not indicated

Route of exposure: Dermal

Results: Negative

Bibliographic reference: Pathology of aging female SENCAR mice used as controls in skin two-stage carcinogenesis studies, Ward J, Quander RD, Wenk M, Spangler E (1986)

METHYL OXIDE DIMETHYLETER

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

N-BUTYL ACETATE

Method: EPA OTS 798.2650

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL = 125 mg / kg bw / day

Method: EPA OTS 798.2450

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEC = 500 ppm

PROPANE

Method: OECD 422

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (gas)

Results: NOAEC 16 000 ppm

2-METHOXY-1-METHYLETHYL ACETATE

BLACK SPRAY CONTROL

Method: OECD Guideline 422

Reliability: 2

Species: Rat (Crj; CD (SD); male / female)

Route of exposure: Oral

Results: NOAEL 1000 mg / kg / day

Method: OECD Guideline 453

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Inhalation (vapors)

Results: NOEL 300 ppm

Method: Equivalent or similar from OECD 410

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: NOAEL > 1 000 mg / kg bw / day

BUTANE

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (gas)

Results: NOAEC = 10000 ppm

ISOBUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

ETHANOL

Method: Equivalent or similar to OECD 408

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL 1 730 mg / kg bw / day

XYLENE (MIXTURE OF ISOMERS)

Method: Equivalent or similar to OECD 408

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: Negative

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

BLACK SPRAY CONTROL

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish	2,6 mg/l/96h
EC50 - for Crustacea	1 mg/l/48h
EC50 - for Algae / Aquatic Plants	1,3 mg/l/72h
EC10 for Algae / Aquatic Plants	0,44 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	0,44 mg/l

N-BUTYL ACETATE

LC50 - for Fish	18 mg/l/96h
EC50 - for Crustacea	44 mg/l/48h
EC50 - for Algae / Aquatic Plants	397 mg/l/72h
EC10 for Algae / Aquatic Plants	196 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	196 mg/l

METHYL OXIDE DIMETHYLETER

LC50 - for Fish	4100 mg/l/96h
EC50 - for Crustacea	4400 mg/l/48h
EC50 - for Algae / Aquatic Plants	154,917 mg/l/72h
Chronic NOEC for Fish	4100 mg/l
Chronic NOEC for Crustacea	4400 mg/l

12.2. Persistence and degradability

ACETONE

Easily degradable in water, 90.9% in 28 days.

N-BUTYL ACETATE

Easily degradable in water, 83% in 28 days.

2-METHOXY-1-METHYLETHYL ACETATE

Rapidly biodegradable, from 70.5% to 93.4% in 45 days.

BUTANE

Quickly degradable in water.

ETHANOL

Quickly biodegradable, 60% in 5 days.

XYLENE (MIXTURE OF ISOMERS)

Rapidly degradable in water, 98% in 28 days

BUTANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

ACETONE

Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)

Solubility in water 100 - 1000 mg/l

Degradability: information not available

BLACK SPRAY CONTROL

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

PROPANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

METHYL OXIDE DIMETHYLETER

Solubility in water 45600 mg/l

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1,09

ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

BCF 25,9

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1,2

PROPANE

Partition coefficient: n-octanol/water 1,09

ETHANOL

Partition coefficient: n-octanol/water -0,35

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

METHYL OXIDE DIMETHYLETER

Partition coefficient: n-octanol/water 0,07 Log Kow

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2,73

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

ACETONE

Incenerire come rifiuto pericoloso secondo le normative locali, statali e federali applicabili. Non gettare nei rifiuti domestici.

METHYL OXIDE DIMETHYLETER

It can be used after reconditioning. In accordance with local and national regulations. It must be incinerated in a suitable incineration plant in possession of an authorization issued by the competent authorities.

2-METHOXY-1-METHYLETHYL ACETATE

This product, when disposed of in its unused and uncontaminated state, must be treated as hazardous waste according to EC Directive 91/689 / EEC. Disposal practices must comply with all national and provincial laws and local or local laws governing hazardous waste. Further evaluation may be required for used, contaminated and residual materials. Do not discharge into sewers, onto the ground or into any body of water.

BUTANE

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

ISOBUTANE

Compliance with local regulations, e.g. incineration through flaring system.

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

BLACK SPRAY CONTROL

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Expl. 1.1	Explosive, division 1.1
Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3

BLACK SPRAY CONTROL

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Press. Gas (Liq.)	Liquefied gas
Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

BLACK SPRAY CONTROL

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.