

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **411 00 15590-3105**
Product name: **OIL FOR FILLETING SPRAY**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Spray lubricant for dies**

1.3. Details of the supplier of the safety data sheet

Name: **Meccanocar Italia S.r.l.**
Full address: **Via San Francesco, 22**
District and Country: **56033 Capannoli (PI)**
Italy
Tel. +39 0587 609433
Fax +39 0587 607145

e-mail address of the competent person
responsible for the Safety Data Sheet

moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to: **National Poisons Information Service: +44 121 507 4123**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Reproductive toxicity, effects on or via lactation	H362	May cause harm to breast-fed children.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

OIL FOR FILLETING SPRAY

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H362	May cause harm to breast-fed children.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P211	Do not spray on an open flame or other ignition source.
P101	If medical advice is needed, have product container or label at hand.
P501	Dispose of contents / container in accordance with local regulations.

Contains:

C-14-17 CLORINATED PARAFFINS

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
C-14-17 CLORINATED PARAFFINS		
CAS 85535-85-9	$45 \leq x < 47,5$	Lact. H362, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH066
EC 287-477-0		
INDEX 602-095-00-X		
Reg. no. 01-2119519269-33-XXXX		
BUTANE		
CAS 106-97-8	$22,5 \leq x < 24$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U
EC 203-448-7		
INDEX 601-004-00-0		
Reg. no. 01-2119474691-32-XXXX		

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

OIL FOR FILLETING SPRAY

ESP España
 FRA France
 GBR United Kingdom
 NOR Norge

TLV-ACGIH

LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
 Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
 EH40/2005 Workplace exposure limits (Third edition, published 2018)
 Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
 ACGIH 2019

C-14-17 CLORINATED PARAFFINS

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,1	mg/l
Normal value in marine water	0,02	mg/l
Normal value for fresh water sediment	13	mg/kg
Normal value for marine water sediment	2,6	mg/kg
Normal value of STP microorganisms	80	mg/l
Normal value for the food chain (secondary poisoning)	10	mg/kg
Normal value for the terrestrial compartment	11,9	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,58 mg/kg bw/d				
Inhalation				2 mg/m3				6,7 mg/m3
Skin				28,75 mg/kg bw/d				47,9 mg/kg bw/d

BUTANE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
WEL	GBR	1450	600	1810	750	
TLV	NOR	600	250			
TLV-ACGIH					1000	

PROPANE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		1000			
TLV	NOR	900	500			
TLV-ACGIH			1000			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

OIL FOR FILLETING SPRAY

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

ISOBUTANE

Suitable glove material protective gloves, e.g. nitrile butadiene rubber gloves (NBR), leather gloves, heat insulating

Selection of protective gloves to meet specific workplace requirements.

Suitability for specific workplaces must be clarified with the manufacturers of protective gloves.

The information is based on our tests, references from literature and information from glove manufacturers or derived by analogy with similar materials.

Remember that the useful time per day of a chemical protection glove can be much shorter than the breakthrough time determined according to EN 374 due to the numerous influencing factors involved.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	aerosol
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C

OIL FOR FILLETING SPRAY

Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,82
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

C-14-17 CLORINATED PARAFFINS

SADT >200°C/392°F.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

C-14-17 CLORINATED PARAFFINS

It can react with alkaline and earth alkaline metals which have a strong affinity for chlorine. It can react with iron, zinc and aluminum at high temperatures leading to decomposition.

ISOBUTANE

Vapors can form an explosive mixture with air.

OIL FOR FILLETING SPRAY

BUTANE

Vapors can form an explosive mixture with air.

10.4. Conditions to avoid

Avoid overheating.

C-14-17 CLORINATED PARAFFINS

Strong oxidizing agents, heat and hot surfaces. Medium chain chlorinated paraffins tend to soften or inflate most gums.

ISOBUTANE

Keep away from heat and other causes of fire.

BUTANE

Avoid heat and sources of ignition.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ISOBUTANE

Strong oxidizing agents, chlorine, oxygen.

BUTANE

Strong oxidizing agents, chlorine, oxygen.

10.6. Hazardous decomposition products

C-14-17 CLORINATED PARAFFINS

Prolonged heating at temperatures in excess of 70 ° C or heating above 200 ° C for short periods will result in the decomposition and release of hydrogen chloride.

ISOBUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO₂).

BUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO₂).

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

C-14-17 CLORINATED PARAFFINS

LD50 (Oral) > 4000 mg/kg Rat - Wistar

LC50 (Inhalation) > 48,17 mg/l Rat

BUTANE

Method: Not indicated

Reliability: 2

Species: Rat (Alderley Park (SPF); male / female)

Route of exposure: Inhalation

Results: LC50: 1 443 mg / L air

PROPANE

Method: To study the concentrations at which the effects of the CNS occur following exposure by inhalation to propane by measuring LC50 (15 min) and EC50 (CNS) (10 min) in rats.

Reliability: 2

OIL FOR FILLETING SPRAY

Species: Rat (Alderley Park (SPF); male / female)
Route of exposure: Inhalation
Results: LC50> 800 000 ppm

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

C-14-17 CLORINATED PARAFFINS

Method: OECD 404
Reliability: 2
Species: Rabbit
Route of exposure: Dermal
Results: Slightly irritating

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

C-14-17 CLORINATED PARAFFINS

Method: Not indicated
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Slightly irritating

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Skin sensitization
C-14-17 CLORINATED PARAFFINS

Method: RAR (EU, 2008)
Reliability: 2
Species: guinea pig
Route of exposure: Dermal
Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

C-14-17 CLORINATED PARAFFINS

Method: Frequency of mutant colonies evaluated in a genetic mutation test (HPRT) with a C10-13 chlorinated paraffin (56% chlorination) - in vitro test
Reliability: 2
Species: Chinese hamster
Results: Negative with or without metabolic activation
Method: Equivalent or similar to OECD 475 in vivo test
Reliability: 2
Species: Rat (Fischer 344; male)
Route of exposure: Oral
Results: Negative

BUTANE

OIL FOR FILLETING SPRAY

Method: OECD 471 in vitro test
Reliability: 1
Species: Salmonella strains, S. typhimurium
Results: Negative without metabolic activation
Method: OECD 474-test in vivo

Reliability: 1
Species: Rat (Sprague-Dawley CD; male / female)
Route of exposure: Inhalation (gas)
Results: Negative

PROPANE

Method: OECD 471 in vitro test
Reliability: 1
Species: Histidine Salmonella
Results: Negative with or without metabolic activation
Method: OECD 474-test in vivo
Reliability: 1
Species: Rat (Sprague-Dawley CD; male / female)
Route of exposure: Inhalation (gas)
Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May cause harm to breast-fed children.

BUTANE

Method: OECD 413
Reliability: 1
Species: Rat (Sprague-Dawley CD; male / female)
Route of exposure: Inhalation
Results: NOAEC 10000 ppm

Adverse effects on sexual function and fertility
C-14-17 CLORINATED PARAFFINS

Method: Equivalent or similar to OECD 414
Reliability: 2
Species: Rabbit (Dutch)
Route of exposure: Oral
Results: NOAEL (development) 100 mg / kg bw / day

PROPANE

Method: OECD 413
Reliability: 1
Species: Rat (Sprague-Dawley CD; male / female)
Route of exposure: Inhalation
Results: NOAEC (fertility) 10 000 ppm

Adverse effects on development of the offspring
C-14-17 CLORINATED PARAFFINS

Method: Equivalent or similar to OECD Preliminary Reproduction Toxicity Screening Test

OIL FOR FILLETING SPRAY

Reliability: 2
Species: Rat (Charles River COBS CD; male / female)
Route of exposure: Oral
Results: NOAEL (fertility) ca. 400 mg / kg bw / day

PROPANE

Method: EPA OPPTS 870.3700
Reliability: 1
Species: Rat (VAF / Plus®, Sprague-Dawley Derived (CD®) CrI: CD® IGS BR)
Route of exposure: Inhalation (gas)
Results: NOAEC (development) 10 426 ppm

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

C-14-17 CLORINATED PARAFFINS

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

ISOBUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

BUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

PROPANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

C-14-17 CLORINATED PARAFFINS

Method: Equivalent or similar to OECD 408
Reliability: 2
Species: Rat (Fischer 344; male / female)
Route of exposure: Oral
Results: NOAEL 300 ppm

ISOBUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

BUTANE

Method: OECD 413
Reliability: 1
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Inhalation (gas)
Results: NOAEC = 10000 ppm

OIL FOR FILLETING SPRAY

PROPANE

Method: OECD 422

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (gas)

Results: NOAEC 16 000 ppm

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

C-14-17 CLORINATED PARAFFINS

LC50 - for Fish

> 5000 mg/l/96h *Alburnus alburnus*

EC50 - for Crustacea

0,0077 mg/l/48h *Daphnia magna*

EC50 - for Algae / Aquatic Plants

> 3,2 mg/l/72h *Pseudokirchnerella subcapitata***12.2. Persistence and degradability**

BUTANE

Quickly degradable in water.

BUTANE

Solubility in water

0,1 - 100 mg/l

Rapidly degradable

PROPANE

Solubility in water

0,1 - 100 mg/l

Rapidly degradable

C-14-17 CLORINATED PARAFFINS

Solubility in water

< 0,1 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water

1,09

PROPANE

Partition coefficient: n-octanol/water

1,09

OIL FOR FILLETING SPRAY

C-14-17 CLORINATED PARAFFINS

Partition coefficient: n-octanol/water 7,2

12.4. Mobility in soil

C-14-17 CLORINATED PARAFFINS

Partition coefficient: soil/water 5

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

ISOBUTANE

Compliance with local regulations, e.g. incineration through flaring system.

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

BUTANE

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

OIL FOR FILLETING SPRAY

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a-E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

OIL FOR FILLETING SPRAY

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Press. Gas (Liq.)	Liquefied gas
Press. Gas	Pressurised gas
Lact.	Reproductive toxicity, effects on or via lactation
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may burst if heated.
H362	May cause harm to breast-fed children.
H400	Very toxic to aquatic life.

OIL FOR FILLETING SPRAY

- H410** Very toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

OIL FOR FILLETING SPRAY

laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 15 / 16.