

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 411 00 08500-2670-White
411 00 08600-2671-Black

Product name: ACRYLIC ANTI-STONE PROTECTIVE SPRAY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Anti-stone protection for bodywork

1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.
Full address: Via San Francesco, 22
District and Country: 56033 Capannoli (PI)
Italy

Tel. +39 0587 609433

Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet

Product distribution by:

moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to

National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P211	Do not spray on an open flame or other ignition source.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE / doctor if you feel unwell.
P501	Dispose of contents / container in accordance with local regulations.

Contains:	HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE METHYL ETHYL KETONE ETHYL ACETATE N-BUTYL ACETATE
------------------	--

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
METHYL OXIDE DIMETHYLETER		
CAS 115-10-6	35 ≤ x < 37,5	Flam. Gas 1A H220, Press. Gas H280

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

EC 204-065-8

INDEX -

Reg. no. 01-2119472128-37-XXXX

ETHYL ACETATE

CAS 141-78-6

8 ≤ x < 9

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4

INDEX 607-022-00-5

Reg. no. 01-2119475103-46-XXXX

METHYL ETHYL KETONE

CAS 78-93-3

8 ≤ x < 9

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 201-159-0

INDEX 606-002-00-3

Reg. no. 01-2119457290-43-XXXX

**HYDROCARBONS, C6,
ISOALKANS, <5% N-HEXANE**

CAS 64742-49-0

7 ≤ x < 8

Asp. Tox. 1 H304, EUH066

EC 931-254-9

INDEX -

Reg. no. 01-2119484651-34-XXXX

N-BUTYL ACETATE

CAS 123-86-4

4 ≤ x < 4,5

Flam. Liq. 3 H226, STOT SE 3 H336, EUH066

EC 204-658-1

INDEX 607-025-00-1

Reg. no. 01-2119485493-29-XXXX

**ETHYLBENZENE AND XYLENE
REACTION MASS**

CAS -

4 ≤ x < 4,5

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315,
Aquatic Acute 1 H400 M=1

EC 905-588-0

INDEX -

Reg. no. 01-2119486136-34-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 36,50 %

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

METHYL OXIDE DIMETHYLETER**Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
			mg/m3	
			ppm	
VLEP	ITA	983	400	INHAL

Predicted no-effect concentration - PNEC

Normal value in fresh water	1,55	mg/l
Normal value in marine water	0,16	mg/l
Normal value for fresh water sediment	6,581	mg/kg
Normal value for marine water sediment	0,69	mg/kg
Normal value for water, intermittent release	1,549	mg/l
Normal value for the terrestrial compartment	0,45	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				471 mg/m3		NPI		1894 mg/m3

METHYL ETHYL KETONE**Threshold Limit Value**

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	600	200	900	300	
VLEP	FRA	600	200	900	300	SKIN
WEL	GBR	600	200	899	300	SKIN
VLEP	ITA	600	200	900	300	
TLV	NOR	220	75			
VLE	PRT	600	200	900	300	
OEL	EU	600	200	900	300	
TLV-ACGIH		590	200	885	300	

Predicted no-effect concentration - PNEC

Normal value in fresh water		55,8		mg/l
Normal value in marine water		55,8		mg/l
Normal value for fresh water sediment		284,74		mg/kg
Normal value for marine water sediment		284,74		mg/kg
Normal value of STP microorganisms		709		mg/l
Normal value for the food chain (secondary poisoning)		1000		mg/kg
Normal value for the terrestrial compartment		22,5		mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				31 mg/kg bw/d				
Inhalation				106 mg/m3				600 mg/m3
Skin				412 mg/kg bw/d				1161 mg/kg bw/d

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	734	200	1468	400	
VLEP	FRA	1400	400			
WEL	GBR	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
TLV	NOR	734	200			
VLE	PRT	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

Normal value in fresh water		0,24		mg/l
Normal value in marine water		0,024		mg/l
Normal value for fresh water sediment		1,15		mg/kg
Normal value for marine water sediment		0,115		mg/kg
Normal value of STP microorganisms		650		mg/l

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Normal value for the food chain (secondary poisoning)	0,2	mg/kg
Normal value for the terrestrial compartment	0,148	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin				37 mg/kg bw/d				63 mg/kg bw/d

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
TLV-ACGIH		1441	400	

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1301 mg/kg bw/d				
Inhalation				1131 mg/m3				5306 mg/m3
Skin				1377 mg/kg bw/d				13964 mg/kg bw/d

ETHYLBENZENE AND XYLENE REACTION MASS

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327	mg/l
Normal value in marine water	0,327	mg/l
Normal value for fresh water sediment	12,46	mg/kg
Normal value for marine water sediment	12,46	mg/kg
Normal value of STP microorganisms	6,58	mg/l
Normal value for the terrestrial compartment	2,31	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				12,5 mg/kg bw/d				
Inhalation	260 mg/m3	260 mg/m3	65,6 mg/m3	65,6 mg/m3	442 mg/m3	442 mg/m3	221 mg/m3	221 mg/m3
Skin				125 mg/kg bw/d				212 mg/kg bw/d

N-BUTYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m3	ppm	
VLA	ESP	724	150	965 200
VLEP	FRA	710	150	940 200
WEL	GBR	724	150	966 200
TLV	NOR		75	

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

TLV-ACGIH	50	150
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,18	mg/l
Normal value in marine water	0,018	mg/l
Normal value for fresh water sediment	0,981	mg/kg
Normal value for marine water sediment	0,098	mg/kg
Normal value of STP microorganisms	35,6	mg/l
Normal value for the terrestrial compartment	0,09	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d				
Inhalation	300 mg/m3	300 mg/m3	35,7 mg/m3	35,7 mg/m3	600 mg/m3	600 mg/m3	300 mg/m3	300 mg/m3
Skin		6 mg/kg bw/d		6 mg/kg bw/d		11 mg/kg bw/d		11 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

ETHYL ACETATE

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Butyl rubber gloves (opening times > 480 minutes), Neoprene™ rubber, nitrile rubber (opening times up to 480 minutes).

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Chemical resistant gloves are recommended. Nitrile, standards CEN EN 420 and EN 374 provide general requirements and lists of types of gloves.

N-BUTYL ACETATE

Wear protective gloves. The recommendations are listed below. Other protective material can be used, depending on the situation, if adequate data on degradation and permeation are available. If other chemicals are used together with this chemical, the selection of materials should be based on the protection of all chemicals present.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid under pressure
Colour	bianco, nero
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	0 °C
Initial boiling point	< -35 °C
Boiling range	Not available
Flash point	< -1 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,91 Kg/l
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 250 °C
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

ETHYL ACETATE

It slowly decomposes to acetic acid and ethanol due to the action of light, air and water. Stable under normal conditions. Upon storage, it is slowly decomposed by water.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

METHYL OXIDE DIMETHYLETER

Vapors can form an explosive mixture with air.

METHYL ETHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

Vapors can form an explosive mixture with air.

10.4. Conditions to avoid

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Avoid overheating.

METHYL OXIDE DIMETHYLETER

Temperature:> 52 ° C

METHYL ETHYL KETONE

Avoid exposure to: sources of heat.

ETHYL ACETATE

Avoid exposure to: light,sources of heat,naked flames.

Ignition sources.

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Open flames and high energy ignition sources.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

Avoid contact with heat, sparks, open flames and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

METHYL OXIDE DIMETHYLETER

Oxygen, oxidizing agents, acid anhydrides, strong acids, carbon monoxide, acetic anhydride, powdered metals.

METHYL ETHYL KETONE

Incompatible with: strong oxidants,inorganic acids,ammonia,copper,chloroform.

ETHYL ACETATE

Incompatible with: acids,bases,strong oxidants,aluminium,nitrates,chlorosulphuric acid.Incompatible materials: plastic materials.

Oxidizing agents, acids, alkalis.

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Strong oxidants.

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

Strong acids and strong bases, strong oxidizing agents.

10.6. Hazardous decomposition products

METHYL OXIDE DIMETHYLETER

Formaldehyde, carbon dioxide (CO₂), carbon monoxide, methanol.

ETHYL ACETATE

Carbon oxides on combustion.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

>2000 mg/kg

METHYL ETHYL KETONE

LD50 (Oral) 2737 mg/kg Rat

LD50 (Dermal) 6480 mg/kg Rabbit

LC50 (Inhalation) 23,5 mg/l/8h Rat

METHYL OXIDE DIMETHYLETER

LC50 (Inhalation) 164000 ppm/4h rat

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

LD50 (Oral) > 25 mg/kg Rat

LD50 (Dermal) > 5 mg/kg Rabbit

LC50 (Inhalation) 73860 ppm/4h Rat

METHYL OXIDE DIMETHYLETER

Method: Not indicated

Reliability: 2

Species: Rat (albino ChR-CD; male)

Route of exposure: Inhalation (gas)

Results: LC50: 164 000 ppm

ETHYL ACETATE

Method: Multi-Substance Rule for the Testing of Neurotoxicity 40 CFR Part 799 (58 FR 40262)

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative

Method: Not indicated

Reliability: 2

Species: Rabbit (New Zealand White; male)

Route of exposure: Dermal

Results: LD50> 20 000 mg / kg bw

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Method: Equivalent or similar to OECD 401
Reliability: 1
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Oral
Results: LD50:> 5 000 mg / kg bw
Method: Equivalent or similar to OECD 403
Reliability: 1
Species: Rat (Crj: CD (SD); male / female)
Route of exposure: Inhalation (vapors)
Results: LC50:> 4 951 mg / m³ air
Method: Equivalent or similar to OECD 402
Reliability: 1
Species: Rat (Crj: CD (SD); male / female)
Route of exposure: Dermal
Results: LD50:> 2 000 mg / kg bw

ETHYLBENZENE AND XYLENE REACTION MASS

Method: Equivalent or similar to EU Method B.2
Reliability: 1
Species: Rat (male)
Route of exposure: Inhalation (vapors)
Results: LC50 6 700 ppm

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 423
Reliability: 2
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Oral
Results: LD50 = 12.2 mL / kg bw
Method: Equivalent or similar to OECD 402
Reliability: 2
Species: Rabbit (New Zealand White; male / female)
Route of exposure: Dermal
Results: LD50> 16 mL / kg bw

SKIN CORROSION / IRRITATION

Causes skin irritation

METHYL ETHYL KETONE

Method: OECD 404
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Not irritating

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: OECD 404
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Irritating

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 404

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Dermal
Results: Not irritating

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

METHYL ETHYL KETONE

Method: Equivalent or similar to OECD 405
Reliability: 2
Species: Rabbit (Albino)
Route of exposure: Ocular
Results: Category 2, irritant

ETHYL ACETATE

Method: OECD 405
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: OECD 405
Reliability: 1
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

N-BUTYL ACETATE

Method: OECD 405
Reliability: 2
Species: Rabbit (New Zealand White)
Route of exposure: Ocular
Results: Not irritating

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: Equivalent or similar to OECD 406
Reliability: 2
Species: guinea pig (Hartley; female)
Route of exposure: Dermal
Results: Not sensitizing

Skin sensitization

METHYL ETHYL KETONE

Method: OECD 406
Reliability: 1
Species: guinea pig (Dunkin-Hartley; female)

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Route of exposure: Dermal
Results: Not sensitizing

ETHYL ACETATE

Method: OECD 406
Reliability: 1
Species: guinea pig (Dunkin-Hartley; female)
Route of exposure: Dermal
Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: OECD 471 in vitro test
Reliability: 1
Species: S. typhimurium
Results: Negative
Method: Equivalent or similar to OECD 477 in vivo test
Reliability: 2
Species: Drosophila melanogaster (male)
Route of exposure: Inhalation (gas)
Results: Negative

METHYL ETHYL KETONE

Method: Equivalent or similar to OECD 471 in vitro test
Reliability: 2
Species: S. typhimurium
Results: Negative
Method: Equivalent or similar to OECD 474 in vivo test
Reliability: 2
Species: Mouse (CD-1; male / female)
Route of exposure: Intraperitoneal
Results: Negative

ETHYL ACETATE

Method: Equivalent or similar to OECD 471 in vitro test
Reliability: 2
Species: S. typhimurium
Results: Negative with and without metabolic activation
Method: Equivalent or similar to OECD 474 in vivo test
Reliability: 2
Species: Chinese hamster (male / female)
Route of exposure: Oral
Results: Negative

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: Equivalent or similar to OECD 471 - in vitro test
Reliability: 1
Species: S. typhimurium
Results: Negative with and without metabolic activation
Method: Equivalent or similar to OECD 474 - in vivo test
Reliability: 1
Species: Mouse (CD-1; male / female)
Route of exposure: Oral

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Results: Negative

ETHYLBENZENE AND XYLENE REACTION MASS

Method: Equivalent or similar OECD Guideline 478-test in vivo

Reliability: 2

Species: Mouse (Swiss Webster; male / female)

Route of exposure: Subcutaneous

Results: Negative

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 471 in vitro test

Reliability: 2

Species: S. typhimurium, E. Coli

Results: Negative with and without metabolic activation

Method: OECD 474-test in vivo

Reliability: 2

Species: Mouse (NMRI; male / female)

Route of exposure: Oral

Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 453

Reliability: 1

Species: Rat (CD (R) (SD) BR; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: Equivalent or similar to OECD 403

Reliability: 1

Species: Rat (F344 / N; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative. The NOAEC for rat females was determined to be 2200 mg / m3. The NOAEC for male rats was determined to be 138 mg / m3.

ETHYLBENZENE AND XYLENE REACTION MASS

Method: Equivalent or similar to EU Method B.32

Reliability: 2

Species: Rat (F344 / N; male / female)

Route of exposure: Oral

Results: Negative

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 452

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Reliability: 1
Species: Rat (CD (SD) BR; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative

ETHYL ACETATE

Method: Equivalent or similar to OECD 416
Reliability: 1
Species: Mouse (CD-1; male / female)
Route of exposure: Oral
Results: Negative
Method: Equivalent or similar to OECD 414
Reliability: 2
Species: Rat (Sprague-Dawley)
Route of exposure: Inhalation
Results: Negative

Adverse effects on sexual function and fertility
METHYL ETHYL KETONE

Method: Equivalent or similar to OECD 416
Reliability: 2
Species: Rat (Wistar; male / female)
Route of exposure: Oral
Results: NOAEL (fertility) 10 000 mg / L

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: OECD TG 413
Reliability: 1
Species: Rat (Fischer 344; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative. NOAEC (fertility) \geq 400 ppm

N-BUTYL ACETATE

Method: OECD 416
Reliability: 1
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative, NOAEC (fertility) = 750 ppm

Adverse effects on development of the offspring
METHYL ETHYL KETONE

Method: Equivalent or similar to OECD 414
Reliability: 1
Species: Rat (Sprague-Dawley)
Route of exposure: Inhalation
Results: NOAEC (development) ca. 1 002 ppm

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: Guidelines for Reproduction Studies for Safety and Evaluation of Drugs for Human Use, Segment II (Teratology Study)
Reliability: 1
Species: Rat (Sprague-Dawley)
Route of exposure: Inhalation (vapors)
Results: Negative. NOAEC (development) $>$ = 300 ppm

ETHYLBENZENE AND XYLENE REACTION MASS

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Method: Equivalent or similar OECD Guideline 414

Reliability: 2

Species: Rat (Sprague-Dawley)

Route of exposure: Inhalation (vapors)

Results: NOAEC 500 ppm

N-BUTYL ACETATE

Method: Equivalent or similar to OECD 414

Reliability: 1

Species: Rat (Sprague-Dawley)

Route of exposure: Inhalation (vapors)

Results: Positive, NOAEC (development) = 1500 ppm

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

METHYL OXIDE DIMETHYLETER

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

METHYL ETHYL KETONE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

ETHYL ACETATE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

ETHYLBENZENE AND XYLENE REACTION MASS

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

N-BUTYL ACETATE

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

Target organ

METHYL ETHYL KETONE

Central nervous system.

ETHYL ACETATE

Central nervous system

N-BUTYL ACETATE

Central nervous system.

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Route of exposure
ETHYL ACETATE

Inhalation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

METHYL OXIDE DIMETHYLETER

Method: Equivalent or similar to OECD 452
Reliability: 1
Species: Rat (CrI: CD (R) (SD) BR; male / female)
Route of exposure: Inhalation (vapors)
Results: Positive, NOAEL = 2.5%

METHYL ETHYL KETONE

Method: Equivalent or similar to OECD 413
Reliability: 1
Species: Rat (Fischer 344; male / female)
Route of exposure: Inhalation (vapors)
Results: NOAEC 5 041 ppm

ETHYL ACETATE

Method: Equivalent or similar to EPA OTS 795.2600
Reliability: 2
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Oral
Results: NOAEL 900 mg / kg bw / day
Method: EPA OTS 798.2450
Reliability: 1
Species: Rat (CrI: CD@BR; male / female)
Route of exposure: Inhalation
Results: LOEC 350 ppm

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Method: Equivalent or similar to OECD 422
Reliability: 1
Species: Rat (Sprague-Dawley; male / female)
Route of exposure: Oral
Results: Negative. NOAEL > = 1000 mg / kg / day
Method: Equivalent or similar to OECD 413
Reliability: 1
Species: Rat (albino; male / female)
Route of exposure: Inhalation (vapors)
Results: Negative. NOAEC = 10186 mg / m3

ETHYLBENZENE AND XYLENE REACTION MASS

Method: Equivalent or similar to EU Method B.32
Reliability: 2
Species: Rat (F344 / N; male / female)
Route of exposure: Oral
Results: NOAEL 250 mg / kg bw / day

ACRYLIC ANTI-STONE PROTECTIVE SPRAY**N-BUTYL ACETATE**

Method: EPA OTS 798.2650

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL = 125 mg / kg bw / day

Method: EPA OTS 798.2450

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative, NOAEC = 500 ppm

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity**N-BUTYL ACETATE**

LC50 - for Fish	18 mg/l/96h
EC50 - for Crustacea	44 mg/l/48h
EC50 - for Algae / Aquatic Plants	397 mg/l/72h
EC10 for Algae / Aquatic Plants	196 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	196 mg/l

METHYL OXIDE DIMETHYLETER

LC50 - for Fish	4100 mg/l/96h
EC50 - for Crustacea	4400 mg/l/48h
EC50 - for Algae / Aquatic Plants	154,917 mg/l/72h
Chronic NOEC for Fish	4100 mg/l
Chronic NOEC for Crustacea	4400 mg/l

ETHYLBENZENE AND XYLENE REACTION**MASS**

LC50 - for Fish	2,6 mg/l/96h
EC50 - for Crustacea	1 mg/l/48h
EC50 - for Algae / Aquatic Plants	1,3 mg/l/72h
EC10 for Algae / Aquatic Plants	0,44 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	0,44 mg/l

12.2. Persistence and degradability**METHYL ETHYL KETONE**

Rapidly degradable in water, 60% in 14 days.

ETHYL ACETATE

Rapidly degradable, 60% in 10 days.

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Rapidly degradable in water, 80% in 28 days.

N-BUTYL ACETATE

Easily degradable in water, 83% in 28 days.

ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

METHYL ETHYL KETONE

Solubility in water > 10000 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

METHYL OXIDE DIMETHYLETER

Solubility in water 45600 mg/l

12.3. Bioaccumulative potential

ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68

BCF 30

METHYL ETHYL KETONE

Partition coefficient: n-octanol/water 0,3

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

METHYL OXIDE DIMETHYLETER

Partition coefficient: n-octanol/water 0,07 Log Kow

12.4. Mobility in soil

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

ACRYLIC ANTI-STONE PROTECTIVE SPRAY**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

METHYL OXIDE DIMETHYLETER

It can be used after reconditioning. In accordance with local and national regulations. It must be incinerated in a suitable incineration plant in possession of an authorization issued by the competent authorities.

ETHYL ACETATE

Dispose of as hazardous waste. Recover or recycle if possible. Otherwise incineration. Dispose according to local regulations.

Disposal of the container: empty the container completely. Empty containers may contain highly flammable residues. Do not cut, grind, puncture, weld or dispose of containers unless adequate precautions have been taken against this hazard. Do not remove the container labels until they are cleaned. Send to drum recovery or metal recovery.

HYDROCARBONS, C6, ISOALKANS, <5% N-HEXANE

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain debris and may be hazardous. Do not attempt to fill or clean containers without proper instructions. Empty drums must be completely drained and stored safely until they are properly reconditioned or disposed of. Empty containers must be recycled, recovered or disposed of through an appropriately qualified or authorized contractor and in accordance with government regulations. DO NOT PRESSURIZE, CUT, WELD, BRAZE, WELD, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY OR OTHER IGNITION SOURCES. MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

- H412** Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

ACRYLIC ANTI-STONE PROTECTIVE SPRAY

laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 15 / 16.