

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**

Code: **411 00 16250-3935**  
Product name: **FUEL INJECTOR CLEANER**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: **Fuel additive**

**1.3. Details of the supplier of the safety data sheet**

Name: **Meccanocar Italia S.r.l.**  
Full address: **Via San Francesco, 22**  
District and Country: **56033 Capannoli (PI)**  
**Italy**

Tel. **+39 0587 609433**Fax **+39 0587 607145**

e-mail address of the competent person

responsible for the Safety Data Sheet: **moreno.meini@meccanocar.it****1.4. Emergency telephone number**For urgent inquiries refer to: **National Poisons Information Service: +44 121 507 4123**

### SECTION 2. Hazards identification

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

## FUEL INJECTOR CLEANER



Signal words:                    Danger

## Hazard statements:

**H226**                    Flammable liquid and vapour.  
**H304**                    May be fatal if swallowed and enters airways.  
**H336**                    May cause drowsiness or dizziness.  
**H411**                    Toxic to aquatic life with long lasting effects.  
**EUH066**                Repeated exposure may cause skin dryness or cracking.

## Precautionary statements:

**P210**                    Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P331**                    Do NOT induce vomiting.  
**P280**                    Wear protective gloves/ protective clothing / eye protection / face protection.  
**P301+P310**            IF SWALLOWED: immediately call a POISON CENTER / doctor.  
**P370+P378**            In case of fire: use CO2 fire extinguisher to extinguish.  
**P261**                    Avoid breathing dust / fume / gas / mist / vapours / spray.

**Contains:**                HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

## 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, &lt;2% AROMATIC</b> CAS 64742-48-9 EC 919-857-5 INDEX - Reg. no. 01-2119463258-33-XXXX	94 ≤ x < 98	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
<b>SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM</b> CAS 64742-94-5 EC 265-198-5 INDEX 649-424-00-3 Reg. no. 01-2119463588-24-XXXX	4 ≤ x < 4,5	Asp. Tox. 1 H304, EUH066

## FUEL INJECTOR CLEANER

**NAPHTHALENE**

CAS 91-20-3

0,85 ≤ x &lt; 0,95 Carc. 2 H351, Acute Tox. 4 H302, Aquatic Chronic 1 H410 M=1

EC 202-049-5

INDEX 601-052-00-2

Reg. no. 01-2119561346-37-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

**EYES:** Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully.

**SKIN:** Remove contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). If exposed: call a poison center or doctor.

**INHALATION:** Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Immediately call a poison center or doctor.

**INGESTION:** Immediately call a poison center or doctor. Induce vomiting if the person is conscious. Rinse your mouth with running water. Do not give anything by mouth to an unconscious person.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

Information not available

### 6.3. Methods and material for containment and cleaning up

Information not available

### 6.4. Reference to other sections

Information not available

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

#### SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers		
	Acute local	Acute systemic	Chronic local		Acute systemic	Chronic local	Chronic systemic
Oral				19 mg/kg bw/d			

## FUEL INJECTOR CLEANER

**NAPHTHALENE**

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,24	mg/l
Normal value in marine water	0,24	mg/l
Normal value for fresh water sediment	6,72	mg/kg
Normal value for marine water sediment	6,72	mg/kg
Normal value of STP microorganisms	2,9	mg/l
Normal value for the terrestrial compartment	5,33	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers			Chronic local	Chronic systemic
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic		
Inhalation							25 mg/m3	25 mg/m3
Skin								3,57 mg/kg bw/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**FUEL INJECTOR CLEANER**

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Chemical resistant gloves are recommended. Nitrile, standards CEN EN 420 and EN 374 provide general requirements and lists of types of gloves.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	clear liquid
Colour	Not available
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	135 °C
Boiling range	220 °C
Flash point	> 35 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	0,6 % (V/V)
Upper explosive limit	7 % (V/V)
Vapour pressure	27 hPa
Vapour density	Not available
Relative density	0,8
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 200 °C
Decomposition temperature	Not available
Viscosity	>5 cSt a 40°
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

VOC (Directive 2010/75/EC) : 95,00 % - 760,00 g/litre

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

May form flammable mixtures with: air.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Avoid heat, sparks, open flames and other sources of ignition.

#### 10.5. Incompatible materials

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Strong oxidants

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

**FUEL INJECTOR CLEANER**ACUTE TOXICITY

LC50 (Inhalation) of the mixture:  
Not classified (no significant component)  
LD50 (Oral) of the mixture:  
Not classified (no significant component)  
LD50 (Dermal) of the mixture:  
Not classified (no significant component)

## SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

LD50 (Oral) &gt; 5000 mg/kg Rat

LD50 (Dermal) &gt; 2000 mg/kg Rabbit

LC50 (Inhalation) &gt; 5,28 mg/l/4h Rat

## HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, &lt;2% AROMATIC

Method: OECD 423  
Reliability: 2  
Species: Rat (Wistar; male / female)  
Route of exposure: Oral  
Results: LD50> 15 000 mg / kg bw  
Method: Equivalent or similar to OECD 403  
Reliability: 1  
Species: Rat (Crj; CD (SD); male / female)  
Route of exposure: Inhalation (vapors)  
Results: LC50> 4 951 mg / m<sup>3</sup> air  
Method: Equivalent or similar to OECD 402  
Reliability: 2  
Species: Rabbit (New Zealand White; male / female)  
Route of exposure: Dermal  
Results: LD50> 5 000 mg / kg bw

## SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Method: EPA OTS 798.1175  
Reliability: 1  
Species: Rat (Sprague-Dawley; male / female)  
Route of exposure: Oral  
Results: LD50:> 5 000 mg / kg bw  
Method: Equivalent or similar to OECD 403  
Reliability: 1  
Species: Rat (Sprague-Dawley; male / female)  
Route of exposure: Inhalation (vapor)  
Results: LC50:> 5.28 mg / L air  
Method: EPA OTS 798.1100  
Reliability: 1  
Species: Rabbit (New Zealand White; male / female)  
Route of exposure: Dermal  
Results: LD50:> 2 000 mg / kg bw

## NAPHTHALENE

Method: OECD 401  
Reliability: 2  
Species: Mouse (CD-1 ICR; male / female)  
Route of exposure: Oral



**FUEL INJECTOR CLEANER**

Results: LD50: 533 mg / kg bw

Bibliographic reference: Shopp GM, White KL, Holsapple MP, Barnes DW, et al., Naphthalene Toxicity in CD-1 Mice: General Toxicology and Immunotoxicology (1984)

Method: Equivalent or similar to OECD 403

Reliability: 1

Species: Rat (Wistar; male / female)

Route of exposure: Inhalation (vapor)

Results: LC50:> 0.4 mg / L air (analytical)

Method: Equivalent or similar to OECD 403

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Dermal

Results: LD50:> 16 000 mg / kg bw

**SKIN CORROSION / IRRITATION**

Repeated exposure may cause skin dryness or cracking.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 404

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Dermal

Results: Irritating

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Method: EPA Guidelines in FR Vol. 44, No. 145, pgs. 44054-44093

Reliability: 2

Species: Rabbit (New Zealand White)

Route of exposure: Dermal

Results: Irritating

NAPHTHALENE

Method: Consumer Product Safety Commission, USA; Code of Federal Regulation, Title 16, Section 1500.41

Reliability: 2

Species: Rabbit (New Zealand White)

Route of exposure: Dermal

Results: Not irritating

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 405

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular

Results: Not irritating

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Method: EPA OTS 798.4500

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular

**FUEL INJECTOR CLEANER**

Results: Not irritating

**NAPHTHALENE**

Method: Consumer Product Safety Commission, USA; Code of Federal Regulation, Title 16, Section 1500.41

Reliability: 2

Species: Rabbit (albino rabbit)

Route of exposure: Ocular

Results: Not irritating

**RESPIRATORY OR SKIN SENSITISATION**

Does not meet the classification criteria for this hazard class

**SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM**

Method: Equivalent or similar to OECD 406-read across

Reliability: 1

Species: guinea pig (Hartley; male)

Route of exposure: Dermal

Results: Not sensitizing

**NAPHTHALENE**

Method: OECD 406

Reliability: 2

Species: guinea pig (Hartley; male)

Route of exposure: Dermal

Results: Not sensitizing

Skin sensitization

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 406

Reliability: 2

Species: guinea pig (Hartley; female)

Route of exposure: Dermal

Results: Not sensitizing

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 471 in vitro test

Reliability: 1

Species: *S. typhimurium*

Results: Negative with or without metabolic activation

Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 1

Species: Mouse (CD-1; male / female)

Route of exposure: Oral

Results: Negative

**SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM**

Method: Equivalent or similar to OECD 479 in vitro test

Reliability: 1

**FUEL INJECTOR CLEANER**

Species: Chinese hamster ovary  
Results: Negative  
Method: Equivalent or similar to OECD 479 in vivo test  
Reliability: 1  
Species: Mouse (B6C3F1; male / female)  
Route of exposure: Oral  
Results: Positive in males, negative in females

**NAPHTHALENE**

Method: Equivalent or similar to OECD 471 in vitro test  
Reliability: 2  
Species: S. typhimurium  
Results: Negative  
Method: EPA OPP 84-2-test in vivo  
Reliability: 1  
Species: Mouse (CD-1; male / female)  
Route of exposure: Oral  
Results: Negative

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC**

Method: Equivalent or similar to OECD 453  
Reliability: 1  
Species: Rat (F344 / N; male / female)  
Route of exposure: Inhalation (vapors)  
Results: NOAEC 138 mg / m<sup>3</sup> air

**NAPHTHALENE**

Method: Not indicated  
Reliability: 1  
Species: Rat (Fischer 344; male / female)  
Route of exposure: Inhalation (vapor)  
Results: Negative

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**NAPHTHALENE**

Method: Equivalent or similar to OECD 413  
Reliability: 1  
Species: Rat (Sprague-Dawley; male / female)  
Route of exposure: Inhalation (vapor)  
Results: Negative

Adverse effects on sexual function and fertility  
**HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC**

Method: OECD TG 413  
Reliability: 1  
Species: Rat (Fischer 344; male / female)  
Route of exposure: Inhalation (vapors)  
Results: NOAEC > = 400 ppm

**FUEL INJECTOR CLEANER**STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

NAPHTHALENE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

Route of exposure

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Dermal and inhalation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 422

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL > = 1000 mg / kg / day

Method: Equivalent or similar to OECD 413

Reliability: 1

Species: Rat (Albino; male / female)

Route of exposure: Inhalation (vapors)

Results: NOAEC 10186 mg / m3

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for repeated exposure.

NAPHTHALENE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

ASPIRATION HAZARD

Toxic for aspiration

**SECTION 12. Ecological information**

**FUEL INJECTOR CLEANER**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

**12.1. Toxicity**

## NAPHTHALENE

EC50 - for Crustacea	2,16 mg/l/48h
EC10 for Algae / Aquatic Plants	16 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	16 mg/l

**12.2. Persistence and degradability**

Petroleum distillates, charcoal, vegetable extracts: they are mixtures of paraffinic, naphthenic, diterpenic and aromatic hydrocarbons. Their behaviour on the environment depends on the concentration. In each case use, according to good working practices, avoiding disposal in the environment. As a rule, the product is poorly biodegradable.

## SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM

Oil distillates, coal, plant extracts: they are blends of parafin hydrocarbons, naphthenes, diterpenes and aromatics. Their behaviour in the environment depends on their composition. In any case they should be used according to good working practice, avoiding discharging it into the environment.

## NAPHTHALENE

Intrinsically biodegradable, 2% in 4 weeks.

SOLVENT NAPHTHA (PETROLEUM),  
HEAVY AROM

Rapidly degradable

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

## CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## NAPHTHALENE

It must comply with local authorities and national legislation. Dispose of as toxic and dangerous waste (Directive 78/319 / EC).

They must not be disposed of with household waste or strong oxidizing agents. Do not allow the product to reach the sewage system.

**SECTION 14. Transport information****14.1. UN number**

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity  $\leq$  5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity  $\leq$  5Kg or 5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity  $\leq$  5Kg or 5L, is not submitted to IATA dangerous goods regulations.

**14.2. UN proper shipping name**

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**14.3. Transport hazard class(es)**

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9

**14.4. Packing group**

FUEL INJECTOR CLEANER

ADR / RID, IMDG, III  
IATA:

14.5. Environmental hazards

ADR / RID: Environmentally  
Hazardous



IMDG: Marine Pollutant



IATA: Environmentally  
Hazardous



14.6. Special precautions for user

ADR / RID: HIN - Kemler: 90

Limited  
Quantities: 5  
L

Tunnel  
restriction  
code: (-)

Special Provision: -

IMDG: EMS: F-A, S-F

Limited  
Quantities: 5  
L

IATA: Cargo:

Maximum  
quantity: 450  
L

Packaging  
instructions:  
964

Pass.:

Maximum  
quantity: 450  
L

Packaging  
instructions:  
964

Special Instructions:

A97, A158,  
A197

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

**SECTION 15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

## FUEL INJECTOR CLEANER

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Carc. 2</b>	Carcinogenicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>H226</b>	Flammable liquid and vapour.
<b>H351</b>	Suspected of causing cancer.
<b>H302</b>	Harmful if swallowed.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals



**FUEL INJECTOR CLEANER**

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.