# Revision nr. 2 Meccanocar Italia S.r.l. Dated 23/06/2020 Printed on 23/06/2020 LIQUID SILICONE Page n. 1/13 Replaced revision:1 (Dated: 02/07/2019)

# **Safety Data Sheet**

According to Annex II to REACH - Regulation 2015/830

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

411 00 09250-2677/1 Code: Product name LIQUID SILICONE

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Lubricant, release agent, water repellent Intended use

# 1.3. Details of the supplier of the safety data sheet

Meccanocar Italia S.r.l. Full address Via San Francesco, 22 District and Country 56033 Capannoli (PI) Italy

Tel. +39 0587 609433

Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet moreno.meini@meccanocar.it

## 1.4. Emergency telephone number

For urgent inquiries refer to National Poisons Information Service: +44 121 507 4123

# **SECTION 2. Hazards identification**

# 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3 H226 Flammable liquid and vapour. Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

# 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

# LIQUID SILICONE

Revision nr. 2

Dated 23/06/2020

Printed on 23/06/2020

Page n. 2/13

Replaced revision:1 (Dated: 02/07/2019)





Signal words: Warning

Hazard statements:

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

**EUH066** Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P331 Do NOT induce vomiting.

**P280** Wear protective gloves/ protective clothing / eye protection / face protection.

P301+P310 IF SWALLOWED: immediately call a POISON CENTER / doctor.

P370+P378 In case of fire: use CO2 fire extinguisher to extinguish.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

Contains: HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

# 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# **SECTION 3. Composition/information on ingredients**

# 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES,

<2% AROMATIC

CAS 64742-48-9 47,5 ≤ x < 50 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066

EC 919-857-5

INDEX -

Reg. no. 01-2119463258-33-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

# | Meccanocar Italia S.r.I. | Revision nr. 2 | | Dated 23/06/2020 | | Printed on 23/06/2020 | | Page n. 3/13 | | Replaced revision:1 (Dated: 02/07/2019)

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

# 5.1. Extinguishing media

## SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

## 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

# 5.3. Advice for firefighters

# GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6. Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

# 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

# Meccanocar Italia S.r.I. Revision nr. 2 Dated 23/06/2020 Printed on 23/06/2020 Page n. 4/13 Replaced revision:1 (Dated: 02/07/2019)

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

# 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Information not available

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

# HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

# SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

# Meccanocar Italia S.r.I. Revision nr. 2 Dated 23/06/2020 Printed on 23/06/2020 Page n. 5/13

Replaced revision:1 (Dated: 02/07/2019)

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Chemical resistant gloves are recommended. Nitrile, standards CEN EN 420 and EN 374 provide general requirements and lists of types of gloves.

# **SECTION 9. Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance liquid Colour colourless typical Odour Odour threshold Not available Not available Melting point / freezing point < -10 °C Initial boiling point 130 °C Boiling range Not available > 36 °C Flash point Evaporation rate Not available Flammability (solid, gas) Not available Lower inflammability limit Not available Not available Upper inflammability limit Lower explosive limit Not available Not available Upper explosive limit Vapour pressure Not available

Solubility insoluble in water

Partition coefficient: n-octanol/water Not available

Auto-ignition temperature > 200 °C

Decomposition temperature Not available

Viscosity >5 cSt a +40 °C

Explosive properties Not available

Oxidising properties Not available

Not available

Vapour density

Relative density

# LIQUID SILICONE

Revision nr. 2

Dated 23/06/2020

Printed on 23/06/2020

Page n. 6/13

Replaced revision:1 (Dated: 02/07/2019)

#### 9.2. Other information

VOC (Directive 2010/75/EC): 50,00 % - 450,00 g/litre

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

# 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

# 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Avoid heat, sparks, open flames and other sources of ignition.

# 10.5. Incompatible materials

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Strong oxidants

# 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

# **SECTION 11. Toxicological information**

# 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

# LIQUID SILICONE

Revision nr. 2

Dated 23/06/2020

Printed on 23/06/2020

Page n. 7/13

Replaced revision:1 (Dated: 02/07/2019)

Information not available

Interactive effects

Information not available

#### ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 423

Reliability: 2

Species: Rat (Wistar; male / female)

Route of exposure: Oral

Results: LD50> 15 000 mg / kg bw

Method: Equivalent or similar to OECD 403

Reliability: 1
Species: Rat (Crj: CD (SD); male / female) Route of exposure: Inhalation (vapors) Results: LC50> 4 951 mg/m³ air

Method: Equivalent or similar to OECD 402

Reliability: 2

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal Results: LD50> 5 000 mg / kg bw

# SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 404

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Dermal

Results: Irritating

# SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 405

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular Results: Not irritating

# LIQUID SILICONE

Revision nr. 2

Dated 23/06/2020

Printed on 23/06/2020

Page n. 8/13

Replaced revision:1 (Dated: 02/07/2019)

#### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Skin sensitization

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 406 Reliability: 2

Species: guinea pig (Hartley; female)

Route of exposure: Dermal Results: Not sensitizing

# GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative with or without metabolic activation Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 1

Species: Mouse (CD-1; male / female)

Route of exposure: Oral Results: Negative

# CARCINOGENICITY

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 453

Reliability: 1

Species: Rat (F344 / N; male / female) Route of exposure: Inhalation (vapors) Results: NOAEC 138 mg / m³ air

# REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

HYDROCARBONS, C9-C11, N-ALCANS, ISÓALKANS, CYCLES, <2% AROMATIC

Method: OECD TG 413

Reliability: 1

Species: Rat (Fischer 344; male / female) Route of exposure: Inhalation (vapors)

Results: NOAEC> = 400 ppm

# STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

# LIQUID SILICONE

Revision nr. 2

Dated 23/06/2020

Printed on 23/06/2020

Page n. 9/13

Replaced revision:1 (Dated: 02/07/2019)

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

Route of exposure

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Dermal and inhalation

# STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

HYDROCARBONS, C9-C11, N-ALCANS, ISOALKANS, CYCLES, <2% AROMATIC

Method: Equivalent or similar to OECD 422

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL> = 1000 mg / kg / day Method: Equivalent or similar to OECD 413

Reliability: 1

Species: Rat (Albino; male / female) Route of exposure: Inhalation (vapors) Results: NOAEC 10186 mg / m3

# **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

# 12.1. Toxicity

Information not available

# 12.2. Persistence and degradability

Information not available

# 12.3. Bioaccumulative potential

Information not available

# 12.4. Mobility in soil

Information not available

# 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

# 12.6. Other adverse effects

	Revision nr. 2
Meccanocar Italia S.r.l.	Dated 23/06/2020
LIQUID SILICONE	Printed on 23/06/2020
	Page n. 10/13
	Replaced revision:1 (Dated: 02/07/2019)
Information not available	
SECTION 13. Disposal considerations	
13.1. Waste treatment methods	
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  CONTAMINATED PACKAGING  Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.	
SECTION 14. Transport information	
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.  14.1. UN number	
Not applicable	
14.2. UN proper shipping name	
Not applicable	
14.3. Transport hazard class(es)	
Not applicable	
14.4. Packing group	
Not applicable	
14.5. Environmental hazards	
Not applicable	

# 

Product

Point

3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

# LIQUID SILICONE

Revision nr. 2

Dated 23/06/2020

Printed on 23/06/2020

Page n. 12/13

Replaced revision:1 (Dated: 02/07/2019)

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3 Asp. Tox. 1 Aspiration hazard, category 1

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### I EGEND.

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

# GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)

# Revision nr. 2 Meccanocar Italia S.r.l. Dated 23/06/2020 Printed on 23/06/2020 LIQUID SILICONE Page n. 13/13 Replaced revision:1 (Dated: 02/07/2019) 15. Regulation (EU) 2018/1480 (XIII Atp. CLP) 16. Regulation (EU) 2019/521 (XII Atp. CLP) - The Merck Index. - 10th Edition - Handling Chemical Safety INRS - Fiche Toxicologique (toxicological sheet) Patty - Industrial Hygiene and Toxicology N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition IFA GESTIS website ECHA website - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy Note for users: The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products. Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9. Changes to previous review: The following sections were modified: 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 15.