Maaaan	ocar Italia S.r.I.	Revision nr. 1		
Weccand		Dated 05/03/2020		
		First compilation		
	OR CRISTAL KIT	Printed on 05/03/2020		
SOLVENT F		Page n. 1/15		
Acco	Safety Data Sheet rding to Annex II to REACH - Regulation 2015/830	I		
SECTION 1. Identification of the sub	ostance/mixture and of the company/under	taking		
1.1. Product identifier Code: Product name	411 00 XXXXXX SOLVENT FOR CRISTAL KIT			
1.2. Relevant identified uses of the substance or Intended use Degreasing solvent	mixture and uses advised against for automotive glass			
1.3. Details of the supplier of the safety data shee	et			
Name Full address District and Country	Meccanocar Italia S.r.I. Via San Francesco, 22 56033 Capannoli (PI) Italy			
	Tel. +39 0587 609433			
	Fax +39 0587 607145			
e-mail address of the competent person				
responsible for the Safety Data Sheet	moreno.meini@meccanocar.it			
1.4. Emergency telephone number For urgent inquiries refer to	National Poisons Information Service: +44 121 507 4123	3		
SECTION 2. Hazards identification				
1. Classification of the substance or mixture				

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

	Meccanoc	ar Italia S.r.I.	Revision nr. 1
			Dated 05/03/2020
			First compilation
	SOLVENT FO	OR CRISTAL KIT	Printed on 05/03/2020
			Page n. 2/15
\wedge	~		
	\checkmark		
Signal words:	Danger		
lazard atatamanta			
azard statements:			
H225	Highly flammable liquid and	vapour.	
H319 H317	Causes serious eye irritation May cause an allergic skin r	n. reaction.	
recautionary statemer	its:		
P210		urfaces, sparks, open flames and other ignition	
P280 P370+P378	Wear protective gloves/ prot In case of fire: use CO2 fire	tective clothing / eye protection / face protectior extinguisher to extinguish.	۱.
P261	Avoid breathing dust / fume	/ gas / mist / vapours / spray.	
P233 P333+P313	Keep container tightly closed If skin irritation or rash occur	o. rs: Get medical advice / attention.	
Contains:	3-TRIMETOSSISILILPROP	AN-1-TIOLO	
.3. Other hazards			
In the basis of availabl	e data, the product does not conta	ain any PBT or vPvB in percentage greater that	n 0,1%.
	omposition/information	on ingredients	
	mposition/information	on ingredients	
SECTION 3. Co	mposition/information	on ingredients	
SECTION 3. Co 3.2. Mixtures ontains:	omposition/information x = Conc. %	on ingredients Classification 1272/2008 (CLP)	
SECTION 3. Co 3.2. Mixtures ontains: Identification			
SECTION 3. Co 3.2. Mixtures ontains: Identification ETHANOL			
SECTION 3. Co 3.2. Mixtures ontains: Identification ETHANOL CAS 64-17-5	x = Conc. %	Classification 1272/2008 (CLP)	
SECTION 3. Co 3.2. Mixtures contains: Identification ETHANOL CAS 64-17-5 EC 200-578-6	x = Conc. % 96 ≤ x < 100	Classification 1272/2008 (CLP)	
SECTION 3. Co 3.2. Mixtures Contains: Identification	x = Conc. % 96 ≤ x < 100	Classification 1272/2008 (CLP)	
SECTION 3. Co 3.2. Mixtures contains: Identification ETHANOL CAS 64-17-5 EC 200-578-6 INDEX 603-002-00-5 Reg. no. 01-211945 3-TRIMETOSSISILIL	x = Conc. % 96 ≤ x < 100 5 7610-43-XXXX	Classification 1272/2008 (CLP)	
SECTION 3. Co 3.2. Mixtures contains: Identification ETHANOL CAS 64-17-5 EC 200-578-6 INDEX 603-002-00-5 Reg. no. 01-211945 3-TRIMETOSSISILILI FIOLO	x = Conc. % 96 ≤ x < 100 5 7610-43-XXXX	Classification 1272/2008 (CLP)	uatic Chronic 2 H411
SECTION 3. Co 3.2. Mixtures contains: Identification ETHANOL CAS 64-17-5 EC 200-578-6 INDEX 603-002-00-5 Reg. no. 01-211945	x = Conc. % 96 ≤ x < 100 5 7610-43-XXXX PROPAN-1-	Classification 1272/2008 (CLP) Flam. Liq. 2 H225, Eye Irrit. 2 H319	uatic Chronic 2 H411

Reg. no. 01-2120763539-41-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

Revision nr. 1

Dated 05/03/2020 First compilation

SOLVENT FOR CRISTAL KIT

Printed on 05/03/2020 Page n. 3/15

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

SOLVENT FOR CRISTAL KIT

Revision nr. 1 Dated 05/03/2020

First compilation

Printed on 05/03/2020

Page n. 4/15

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP FRA GBR NOR	España France United Kingdom Norge TLV-ACGIH	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST) Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS EH40/2005 Workplace exposure limits (Third edition,published 2018) Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5 ACGIH 2019

ETHANOL						
Threshold Limit Value						
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	

Revision nr. 1

Dated 05/03/2020

SOLVENT FOR CRISTAL KIT

First compilation Printed on 05/03/2020

Page n. 5/15

VLA ESP 1910 1000 VLEP FRA 1900 1000 9600 5000 WEL GBR 1920 1000 5000 5000 TLV NOR 950 500 5000 5000 TLV-ACGIH NOR 950 500 500 500 Predicted no-effect concentration - PNEC 1884 1000 500 500 Normal value in fresh water 0.96 mg/l 500 500 Normal value for fresh water sediment 3.6 mg/kg 500 500 Normal value for the tood chain (secondary poisoning) 580 mg/l 500 500 Normal value for the tood chain (secondary poisoning) 0.63 mg/kg 500 500 Normal value for the tood chain (secondary poisoning) 0.63 mg/kg 500 500 Normal value for the tood chain (secondary poisoning) 0.63 mg/kg 500 500 500 500 500 500 500 500 500 500									
WEL GBR 1920 1000 TLV NOR 950 500 TLV-ACGIH 1884 1000 Predicted no-effect concentration - PNEC 1884 1000 Normal value in fresh water 0,96 mg/l Normal value in fresh water sediment 0,79 mg/l Normal value for fresh water sediment 3,6 mg/kg Normal value of STP microorganisms 580 mg/l Normal value for the tord chain (secondary poisoning) 0,38 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Normal value of STP microorganisms Seffect son consumers Route of exposure Acute systemic Chronic local Acute systemic Oral Seffect son systemic Seffect son systemic	VLA	ESP			1910	1000			
TUV NOR 950 500 TLV-ACGIH 1884 1000 Predicted no-effect concentration - PNEC Normal value in fresh water 0,96 mg/l Normal value in fresh water sediment 0,79 mg/kg Normal value for fresh water sediment 3,6 mg/kg Normal value for marine water sediment 2,9 mg/kg Normal value for the food chain (secondary poisoning) 0,88 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Stein consumers Effects on consumers systemic systemi	VLEP	FRA	1900	1000	9500	5000			
TU-ACGIH 1884 1000 Predicted no-effect concentration - PNEC 0.96 mg/l Normal value in fresh water 0.79 mg/l Normal value for fresh water sediment 3.6 mg/kg Normal value for fresh water sediment 2.9 mg/kg Normal value for fresh water sediment 2.9 mg/kg Normal value for the food chain (secondary poisoning) 0.38 mg/kg Normal value for the terrestrial compartment 0.63 mg/kg Normal value for the terrestrial compartment Systemic Chronic local Kronic Normal value for the terrestrial compartment Systemic Systemic Systemic Stin 343 mg/kg Systemic Systemic Systemic <td>WEL</td> <td>GBR</td> <td>1920</td> <td>1000</td> <td></td> <td></td> <td></td> <td></td> <td></td>	WEL	GBR	1920	1000					
Predicted no-effect concentration - PNEC Normal value in fresh water 0,96 mg/l Normal value in marine water 0,79 mg/l Normal value for fresh water sediment 3,6 mg/kg Normal value for fresh water sediment 2,9 mg/kg Normal value for the food chain (secondary poisoning) 0,38 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL / Effects on consumers Effects on systemic Chronic local Acute local Acute systemic Chronic local Systemic Systemic Oral Acute local Acute local Acute local Acute local Systemic More systemic Systemic Systemic Skin 206 mg/kg 343 mg/kg 343 mg/kg Arter to constration - PNEC Systemic More avalue in fresh water 0,005 mg/l Normal value in fresh water 0,005 mg/l Image avalue in marine water sediment 0,002 mg/kg Normal value in fresh water sediment 0,002 mg/kg Image avalue in fresh water sediment Image avalue in fre	TLV	NOR	950	500					
Normal value in fresh water 0,96 mg/l Normal value in marine water 0,79 mg/l Normal value for fresh water sediment 3,6 mg/kg Normal value for fresh water sediment 2,9 mg/kg Normal value for the food chain (secondary poisoning) 0,38 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on consumers Effects on consumers Chronic local Acute local Acute local Acute local Acute systemic Systemic systemic Systemic systemic Systemic systemic Systemic systemic systemic Systemic systemic Systemic systemic Systemic systemic Systemic systemic Systemic systemic Systemic systemic systemic Systemic systemic Systemic systemic Systemic systemic Systemic systemic systemic Systemic systemic systemic Systemic systemic systemic Systemic systemic systemic systemic Systemic systemic systemic Systemic systemic systemic systemic systemic systemic systemic Systemic s	TLV-ACGIH				1884	1000			
Normal value in marine water 0,79 mg/l Normal value for fresh water sediment 3,6 mg/kg Normal value for marine water sediment 2,9 mg/kg Normal value for the food chain (secondary poisoning) 0,38 mg/kg Normal value for the food chain (secondary poisoning) 0,63 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on workers Chronic consumers Chronic systemic Acute local Acute systemic Chronic local Systemic Sy	Predicted no-effect concentration	ion - PNEC							
Normal value for fresh water sediment 3.6 mg/kg Normal value for marine water sediment 2.9 mg/kg Normal value of STP microorganisms 580 mg/l Normal value for the food chain (secondary poisoning) 0.38 mg/kg Normal value for the terrestrial compartment 0.63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on systemic Chronic local systemic Acute local systemic Acute systemic Ohronic local systemic Chronic local systemic Chronic local systemic Chronic systemic Chronic local systemic Chronic systemic Chronic local systemic Chronic systemic Systemic Syste	Normal value in fresh water				0,96	mg	/I		
Normal value for marine water sediment 2,9 mg/kg Normal value of STP microorganisms 580 mg/l Normal value of STP microorganisms 0,38 mg/kg Normal value for the food chain (secondary poisoning) 0,38 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on consumers Effects on workers Acute local Acute systemic Acute local Acute systemic Acute local Acute systemic Acute local Chronic local Chronic local Chronic local Chronic local Systemic Systemic <td>Normal value in marine water</td> <td></td> <td></td> <td></td> <td>0,79</td> <td>mg</td> <td>/I</td> <td></td> <td></td>	Normal value in marine water				0,79	mg	/I		
Normal value of STP microorganisms 580 mg/l Normal value for the food chain (secondary poisoning) 0,38 mg/kg Normal value for the food chain (secondary poisoning) 0,63 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on workers Effects on workers Chronic local Acute Route of exposure Acute local Acute systemic Chronic local Chronic systemic Syst	Normal value for fresh water se	ediment			3,6	mg	/kg		
Normal value for the food chain (secondary poisoning) 0,38 mg/kg Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on consumers Effects on consumers Effects on workers Route of exposure Acute local Acute systemic Chronic local Chronic systemic	Normal value for marine water	sediment			2,9	mg	/kg		
Normal value for the terrestrial compartment 0,63 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on workers Route of exposure Acute local Acute systemic Oral 87 mg/kg Inhalation 114 mg/m3 950 mg/m3 Skin 206 mg/kg 343 mg/kg Dy/d 500 mg/m3 343 mg/kg Skin 206 mg/kg 343 mg/kg Dy/d 950 mg/m3 343 mg/kg Skin 206 mg/kg 343 mg/kg Dy/d 950 mg/m3 343 mg/kg Skin 206 mg/kg 343 mg/kg Dy/d 950 mg/m3 950 mg/m3 Skin 206 mg/kg 343 mg/kg Dy/d 950 mg/m3 950 mg/m3 Skin 206 mg/kg 343 mg/kg Dy/d 950 mg/m3 950 mg/m3 Skin 206 mg/kg 940 mg/kg Dy/d 950 mg/m3 950 mg/m3 Skin 206 mg/kg 940 mg/kg Dy/d 950 mg/m3 950 mg/m3 Skin 206 mg/kg 940 mg/kg Normal value in fresh water 0,005 mg/l Normal value for fresh water sediment 0,02 mg/kg Normal value	Normal value of STP microorg	anisms			580	mg	/I		
Health - Derived no-effect level - DNEL / DMEL Effects on consumers Effects on workers Route of exposure Acute local Acute systemic Chronic local Chronic systemic Acute local Acute Systemic Chronic local Chronic systemic Chronic systemic Sys	Normal value for the food chain	n (secondary poison	ing)		0,38	mg	/kg		
Effects on consumers Effects on workers Route of exposure Acute local Acute systemic Chronic local Sute of exposure Acute local Acute systemic Chronic local Chronic systemic S	Normal value for the terrestrial	compartment			0,63	mg	/kg		
Route of exposureAcute localAcute systemicChronic localAcute localAcute systemicChronic localChronic systemicOral87 mg/kg87 mg/kg87 mg/kg87 mg/kg87 mg/kg950 mg/m3Inhalation114 mg/m3950 mg/m3950 mg/m3943 mg/kg943 mg/kgSkin206 mg/kg206 mg/kg343 mg/kg96/mg/kg3-TRIMETOSSISILILPROPAN-1-TIOLOPredicted no-effect concentration - PNEC9005mg/lNormal value in fresh water0,005mg/l11Normal value in marine water0,002mg/kg11Normal value for fresh water sediment0,002mg/kg11Normal value of STP microorganisms2,6mg/l11	Health - Derived no-effec	Effects on	MEL						
Inhalation 114 mg/m3 950 mg/m3 Skin 206 mg/kg bw/d 343 mg/kg bw/d 3-TRIMETOSSISILILPROPAN-1-TIOLO 206 mg/kg 343 mg/kg Predicted no-effect concentration - PNEC 0,005 mg/l Normal value in fresh water 0,001 mg/l Normal value for fresh water sediment 0,02 mg/kg Normal value for marine water sediment 0,002 mg/kg Normal value of STP microorganisms 2,6 mg/l	Route of exposure		Acute systemic	Chronic local				Chronic local	
Skin 206 mg/kg bw/d 343 mg/kg bw/d 3-TRIMETOSSISILILPROPAN-1-TIOLO Predicted no-effect concentration - PNEC 0,005 mg/l Normal value in fresh water 0,005 mg/l Normal value in marine water 0,001 mg/l Normal value for fresh water sediment 0,02 mg/kg Normal value of STP microorganisms 2,6 mg/l	Oral								
3-TRIMETOSSISILIPROPAN-1-TIOLO bw/d bw/d bw/d Predicted no-effect concentration - PNEC 0,005 mg/l Normal value in fresh water 0,001 mg/l Normal value for fresh water sediment 0,02 mg/kg Normal value for marine water sediment 0,002 mg/kg Normal value of STP microorganisms 2,6 mg/l	Inhalation				114 mg/m3				950 mg/m3
Predicted no-effect concentration - PNEC Normal value in fresh water 0,005 mg/l Normal value in marine water 0,001 mg/l Normal value for fresh water sediment 0,02 mg/kg Normal value of STP microorganisms 2,6 mg/l	Skin								
Normal value in fresh water0,005mg/lNormal value in marine water0,001mg/lNormal value for fresh water sediment0,02mg/kgNormal value for marine water sediment0,002mg/kgNormal value of STP microorganisms2,6mg/l									
Normal value in marine water 0,001 mg/l Normal value for fresh water sediment 0,02 mg/kg Normal value for marine water sediment 0,002 mg/kg Normal value of STP microorganisms 2,6 mg/l		ion - PNEC							
Normal value for fresh water sediment0,02mg/kgNormal value for marine water sediment0,002mg/kgNormal value of STP microorganisms2,6mg/l	Normal value in fresh water				,	mg	/I		
Normal value for marine water sediment 0,002 mg/kg Normal value of STP microorganisms 2,6 mg/l	Normal value in marine water				0,001	mg	/I		
Normal value of STP microorganisms 2,6 mg/l	Normal value for fresh water se	ediment			0,02	mg	/kg		
	Normal value for marine water	sediment			0,002	mg	/kg		
Normal value for the terrestrial compartment 0,001 mg/kg	Normal value of STP microorg	anisms			2,6	mg	/I		
	Normal value for the terrestrial	compartment			0,001	mg	/kg		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

Revision nr. 1

Dated 05/03/2020 First compilation

SOLVENT FOR CRISTAL KIT

Printed on 05/03/2020 Page n. 6/15

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

3-TRIMETOSSISILILPROPAN-1-TIOLO

Hand protection: protective gloves according to EN 374. Glove material: plastic or rubber. Observe the glove manufacturer's instructions regarding penetrability and breakthrough time. Eye protection: watertight protective goggles according to EN 166.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

SS
lable
lable
lable
//V)
/V)
lable

Revision nr. 1 Dated 05/03/2020

First compilation

Printed on 05/03/2020

Page n. 7/15

SOLVENT FOR CRISTAL KIT

Upper explosive limit	Not available
Vapour pressure	59 hPa
Vapour density	Not available
Relative density	0,8 g/ml
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 200 °C
Decomposition temperature	Not available
Viscosity	1,5 mPa.s
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

3-TRIMETOSSISILILPROPAN-1-TIOLO

Sensitive to humidity.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHANOL

Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANOL

Avoid exposure to: sources of heat,naked flames.

High temperature. Proximity to sources of ignition

SOLVENT FOR CRISTAL KIT

Revision nr. 1 Dated 05/03/2020 First compilation

Printed on 05/03/2020

Page n. 8/15

3-TRIMETOSSISILILPROPAN-1-TIOLO

Keep away from heat, sparks and open flame. Protect from light. Protect from moisture and water.

10.5. Incompatible materials

ETHANOL

strong mineral acids, oxidizing agents. Aluminum at higher temperatures.

3-TRIMETOSSISILILPROPAN-1-TIOLO

Water, acids, alkalis.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANOL

Combustion will generate carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Meccanocar Italia S.r.I.	Revision nr. 1
	Dated 05/03/2020
	First compilation
SOLVENT FOR CRISTAL KIT	Printed on 05/03/2020
	Page n. 9/15

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: >2000 mg/kg LD50 (Dermal) of the mixture: Not classified (no significant component)

ETHANOL

LD50 (Oral) > 5000 mg/kg Rat

LC50 (Inhalation) 120 mg/l/4h Pimephales promelas

3-TRIMETOSSISILILPROPAN-1-TIOLO

Method: Equivalent or similar to OECD Guideline 401 Reliability: 2 Species: Rat (Sprague-Dawley; male / female) Route of exposure: Oral Results: LD50 ca. 0.88 mL / kg bw Method: Equivalent or similar to OECD Guideline 402 Reliability: 2 Species: Rabbit (New Zealand White; male / female) Route of exposure: Dermal Results: LD50 ca. 2.46 mL / kg bw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

ETHANOL

Method: OECD 404 Reliability: 1 Species: Rabbit (New Zealand White) Route of exposure: Dermal Results: Not irritating

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Skin sensitization 3-TRIMETOSSISILILPROPAN-1-TIOLO

Method: OECD Guideline 406 Reliability: 1 Species: guinea pig (Dunkin-Hartley; male)

Meccanocar Italia S.r.I.	Revision nr. 1
	Dated 05/03/2020
	First compilation
SOLVENT FOR CRISTAL KIT	Printed on 05/03/2020
	Page n. 10/15

Route of exposure: Dermal Results: Positive, category 1B

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

ETHANOL

Method: Equivalent or similar to OECD 478 in vivo test Reliability: 2 Species: Mouse (CFLP and Alderley Park; male) Route of exposure: Oral Results: Negative

3-TRIMETOSSISILILPROPAN-1-TIOLO

Method: OECD Guideline 471-in vitro test Reliability: 1 Species: S. typhimurium Results: Negative with or without metabolic activation

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on development of the offspring ETHANOL

Method: Not indicated Reliability: 2 Species: Rat (Sprague-Dawley) Route of exposure: Oral Results: NOAEL (development) 5.2 g ethanol / kg bw / day Bibliographic reference: Prenatal ethanol exposure has differential effects on fetal growth and skeletal ossification, Simpson ME, Duggal S, & Keiver K (2005)

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

ETHANOL

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

3-TRIMETOSSISILILPROPAN-1-TIOLO

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Revision nr. 1 Dated 05/03/2020

First compilation

SOLVENT FOR CRISTAL KIT

Printed on 05/03/2020

Page n. 11/15

ETHANOL

Method: Equivalent or similar to OECD 408 Reliability: 2 Species: Rat (Sprague-Dawley; male / female) Route of exposure: Oral Results: NOAEL 1 730 mg / kg bw / day

3-TRIMETOSSISILILPROPAN-1-TIOLO

Based on available data and expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

3-TRIMETOSSISILILPROPAN-1-TIOLO	
LC50 - for Fish	345 mg/l/96h
EC50 - for Crustacea	5,3 mg/l/48h
EC50 - for Algae / Aquatic Plants	732 mg/l/72h
EC10 for Algae / Aquatic Plants	72 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	72 mg/l
12.2. Persistence and degradability	
ETHANOL Quickly biodegradable, 60% in 5 days.	
ETHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable 12.3. Bioaccumulative potential	
12.5. Bioaccumulative potential	
ETHANOL	
Partition coefficient: n-octanol/water	-0,35
12.4. Mobility in soil	
Information not available	
12.5. Results of PBT and vPvB assessment	

Revision nr. 1 Dated 05/03/2020

SOLVENT FOR CRISTAL KIT

First compilation Printed on 05/03/2020

Page n. 12/15

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Meccanocar Italia S.r.I.	Revision nr. 1
	Dated 05/03/2020
	First compilation
SOLVENT FOR CRISTAL KIT	Printed on 05/03/2020
	Page n. 13/15

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point

3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Revision nr. 1 Dated 05/03/2020

SOLVENT FOR CRISTAL KIT

First compilation Printed on 05/03/2020

Page n. 14/15

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- **OEL: Occupational Exposure Level**
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- Regulation (EC) 1272/2008 (CLP) of the European Parliament
 Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament

Revision nr. 1

Dated 05/03/2020 First compilation

Printed on 05/03/2020

Page n. 15/15

SOLVENT FOR CRISTAL KIT

- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP) 15. Regulation (EU) 2018/1480 (XII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.