# **Technical Information**



Nonfood Compounds Program Listed H1 Registration Number 139225

Product name : MoTip Food Grade Vaseline

**Article number** : **005010** Meccanocar code: 411 00 20760-6386

Supplier / Producer : MOTIP DUPLI B.V.

Wolfraamweg 2

**NL-8471 XC WOLVEGA** 

Telephone number +31 561 - 69 44 00 Telefax number +31 561 - 69 44 31

# **Product description**

High quality viscous lubricant and preservative. Vaseline can be processed as grease with the lubricating properties of oil. In view of the unique formula, suitable for use in the food industry, in accordance with NSF registration H1.

## **Applications**

Battery poles Fasteners (screws, bolts and nuts) Electrical Connections Conveyors Rails

### **Product characteristics**

National Sanitation Foundation registration NSF-H1, number 139225
Water-repellent
Excellent adhesion
Prevents wear and sticking
Resistant to weather influences
Resistant to salt water, weak acids and bases
Excellent corrosion prevention
Misty spray pattern
360° Valve

### **Physical and Chemical Characteristics**

Contents : 500 ml Basis : Vaseline

VOC-content : Approximately 85% w/w

Colour : White

Scent Characteristic Relative density at 20°C 0,66 g/ml 1,1 g/sec Yield 3 to 4 bar Vapour pressure at 20°C 4 Ball EP-test (ASTM D 2596) 3136 N 4 Ball Wear-test (ASTM D 2266) < 0.4 mmDrop point 42°C - 60°C -30°C tot +160°C Temperature resistant

pH value : Neutral

# Vaseline Vazelina Vaselina Vas

# Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol.

Apply the vaseline in a thin layer.



May 25, 2007

Mr. H.J. Hoogenberg MOTIP DUPLI B.V. **WOLFRAAMWEG 2** 8471 XC WOLVEGA THE NETHERLANDS

RE: VASELINE (Aerosol) Category Code: H1 NSF Registration No. 139225

Dear Mr. H.J. Hoogenberg:

NSF has processed the application for Registration of VASELINE (Aerosol) to the NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds (2007), which are available at www.nsfwhitebook.org. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling review.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (www.nsfwhitebook.org). The NSF Registration Mark can be downloaded by clicking the "Download Registration Mark" link on the NSF website (www.nsfwhitebook.org).

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at www.nsfwhitebook.org. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Jennifer De France

Gender De Lanne

NSF Nonfood Compounds Registration Program

Company No: 4C240