

meccanocar Blue stringy adhesive grease CM54

411 00 16590-4110-600 g – 411 00 17430-4355-400 g

411 00 16595-4111-24 Kg

Description

Special grease resistant to high temperatures and high loads even in the presence of high humidity or run-off problems.

Property

- Excellent adhesiveness.
- Very high degree of water repellency.
- Excellent filamentosity.
- Absence of graphite.
- Absence of Molybdenum Bisulphide.

Uses

The blue CM54 Meccanocar stringy grease consists of a very high viscosity base oil thickened with special complex aluminum soaps, antioxidant, anti-rust, anti-friction and special additives tackiness.

It is ideal for the lubrication of heavy construction machinery (hammers, shears, cranes, conveyor belts etc.) and for the lubrication of earth moving machines, tractors, etc.

Particularly suitable also for bearings, in particular where strong adhesiveness is required.

The blue stringy grease CM54 Meccanocar guarantees lubrication intervals up to 5 times longer than traditional greases.

Chemical-physical characteristics

Characteristics	Methods	U.M.	Values
Colour	Visual		Blue
Appearance	Visual		Bright pasty
Penetration	Proc. 60 double hits	mm/10	265/295
Drop point	ASTM D 566	°C	250
Timken	Load	Lbs	>40

Subject to modifications