

meccanocar 411 00 20800-Universal grease (screw cartridge)

Description

Lubricating grease based on lithium soaps, universal use for all flat, rolling and plain bearings.

It is a grease with good mechanical stability, good oxidation resistance, uniform behavior at various temperatures within the indicated working thermal range. It also ensures fair resistance to water and humidity.

Use

Meccanocar multipurpose grease is formulated for universal use in industry, in the trucking, agriculture, earthmoving and construction sectors.

It is also used conveniently in humid or dusty environments where grease must protect the friction points from the penetration of water and impurities and from corrosion.



Characteristics

- Good adhesive power
- Resistant to oxidation
- Good water resistance
- Excellent anticorrosive power

Physical and chemical characteristics

Continuous thermal working range		°C	-25/+120
Max temperature for short periods		°C	+130
Drip point	DIN ISO 2176	°C	>185
Penetration worked	DIN ISO 2137	1/10 min	265-295
NLGI class			2
Thickener			Li 12-Idrossistearat
Base oil viscosity	DIN 51 562	mm ² /s	135
Water resistance	DIN 51 807 T1	grade	1-90
Corrosion protection	DIN 51 802	grade	0
Corrosion on copper	DIN 51 811	grade	1-100
Classification	DIN 51 502		K 2 K-20

Subject to modification