



meccanocar 411 00 15280-P.T.F.E. Oily lubricant

Physical and chemical properties

- Composition: PTFE, silicone, petroleum jelly and solvents.
- Propellant: mixture of G.P.L.
- Appearance and color: straw-colored liquid under pressure.
- Flammability: Extremely flammable.
- Water solubility: NO.
- Lipid: YES.

Characteristics

Product used for the lubrication of parts to which it is not appropriate to use conventional greases. Suitable for fine mechanics, musical instruments, military equipment, optical equipment (cameras, binoculars), nautical equipment, etc. In processing does not interact with the finishing touches such as printing, coating, metallization, bonding.

Use

Spray the product from a distance of about 20 cm. on the treated, it forms a film thin allowing use even in cases where tolerances are minimal. Thanks to the special dispenser, you can reach even the most difficult.

Shelf life

Minimum 36 months in conditions of temperature from +5 / +30 ° C. Protect from moisture.

Care

Pressurized container. Protect from sunlight and do not expose to temperatures above 50 ° C. Do not spray on a naked flame or any incandescent material. Do not pierce or burn, even after use. Avoid direct inhalation or spray into the eyes. Keep away from any source of combustion. Do not smoke. Keep out of reach of children. Avoid the accumulation of electrostatic charges. Apply the product in the quantities strictly necessary. An excess amount of the air may give rise to the formation of any accumulation of gas flammable. Operate in a well ventilated or air the room immediately after use.

HAZARDS: remember that the container is a pressurized container. THE PRODUCT IS IRRITATING TO SKIN.