

Control black spray-Technical data sheet. Page 1 of 1 03/03/2010

meccanocar 411 00 19200-5835-Control black spray

Description

Control paint, fast-drying, acrylic, for the detection of imperfections, pores, irregularities and sanding marks on fillers and putties in the body.

Equipped with adjustable spray head in a fan for a quick convenient application.

The black light is a system that quickly and easily allows you to highlight the parties do not perfectly sanded: imperfections, pores, irregularities and sanding marks.

Use

- Shake the can for at least two minutes since you perceive well the inner spheres. Make spray and check the color obtained.
- > Spray a light hand from a distance of about 20-25 cm from the surface to control. The paint can be sanded after 2-3 minutes.
- > After use invert the can and spray to clean the valve thoroughly. Removing the product with acetone or nitro.

Physical and chemical properties

General information.

Forme: Aerosol

Color: In accordance with the designation of the product

Odour: Caracteristic

Change of state.

Melting point / Melting range: Undefined

Boiling point / Boiling range: Not applicable, because is an aerosol Flash point: Not applicable, because is an aerosol

Self ignition: Not applicable

Danger of explosion: In use, may form explosive mixture with air/vapor

Flammabilty limits:

Lower: 1,2 Vol % Upper: 13,0 Vol %

Vapour tension at 20°C: 8300 hPa Density at 20°C: 0,79 g/cm³

Solubility with water: Little and/or immiscible

VOC (EU): 748,9 g/l

Storage and shelf life

The product has a useful life of more than 10 years when stored properly, with temperatures between +10 and+25 ° C, 60% relative humidity.