

Anti-slag paste-Technical data sheet. Page 1 of 1

meccanocar 411 00 15230-2874-Anti-slag paste.

FIELD OF USE:

For protecting burner nozzles and contact points for electrode and inert gas welding.

DESCRIPTION:

Meccanocar 411 00 15230-2874 is a detacher with a special mineral grease base, without silicone, for the welding technique. It prevents welding drippings from adhering to the burner tips (prevents the formation of encrustations) and considerably prolongs life of the nozzles and contact points

ADDITIONAL INFORMATION:

- > Prevents the formation of encrustations.
- Odourless.
- > Without solvents.
- Non flammable.

Product for professional use.

TECHNICAL SPECIFICATIONS:

- > Appearance: green paste.
- Density: 0.93 g/cc +/+- 0.05 at 20°C.
- > Propellant: DME.

Containers: 450 gr. tin can.

Maximum storage life: 1 year.

USE AND DOSES:

Briefly immerse the burner nozzle into the product.

Read and follow the safety warnings the container label.

For information regarding handling, transportation, etc., consult the Safety Sheet concerning the product in question.

The information appearing in this documentation refers to knowledge of the product upon the date of compilation indicated above.

In consideration of the many possible uses, and possible interference from elements not depending on the manufacturer, we cannot assume any responsibility in merit of the instructions shown.